

ArcelorMittal Dofasco G.P.  
P.O. Box 2460  
Hamilton, Ontario  
L8N 3J5

TEST REPORT  
RAPPORT D'ESSAI

Attention: [NAME]  
Fax: [FAX]  
Date: 12/06/2019

-Purchase Order/Bon de Commande- -Customer/Client- -Sales Order/Bon de Commande- -Vendor/Vendeur-  
AMMEX-DOFASCO-001 002050 HS2 393061001  
-Bill of Lading/Connaissance- -Packing Slip/Bordereau de Charge- -Vehicle or Carrier/Vehicule ou Transporteur-  
557273 CNRAIL

-Sold To/Vendu A- -Ship To/Expedier A-  
ARCELORMITTAL MEXICOS.A. DE C.V ARCELORMITTAL MEXICOMONTERREY  
1G FRANCISCO J'MUGICA 28.2 C.A.V. LIBR. NORESTE  
LAZARO CARDENAS, MICHOACAN ESCOBEDO, NUEVO LEON  
MEXICO 60950 MEXICO 66050  
SACHIN BHATT

-Spec/Norm et Spec- -Material Description/Description du Material-  
STANDARD THICKNESS TOLERANCE HOT ROLLED STEEL SHEET  
SAE J 403 GRADE 1010 B (JUN2014) COMMERCIAL STEEL  
STANDARD UNEXPOSED SURFACE COILS  
MATERIAL CERTIFICATION REQUIRED MILL EDGE PLAIN DRY  
Code: 45-99

.0747 X 48 X COIL  
WEIGHT: 42330 LBS  
-Test Methods/Methods d'Essai-  
ASTM E1019, E415

-----

HEAT Chemical testing performed by an ISO/IEC 17025 certified laboratory

COULEE	C	Mn	P	S	Si	Cu	Ni	Cr	Sn	Mo	Als	Alt	Cb	V	Ti	Ca	N	B	O
760682	.09	.34	.005	.005	.02	.05	.01	.03	.002	.005	.036	.039	.001	.001	.001	.0002	.0029	.0000	

-----

SERIAL NUMBER LIFT #  
NOMBRE DE SERIE FARDEAU  
F36364/00 5030604  
-----

We Certify That The Material Described Herein Conforms To The Specification Shown On This Document  
As shipped from ArcelorMittal Dofasco G.P. as per John Duric - CMTL Supervisor 905-548-7200 x 6960  
The Results Relate Only To The Items Tested  
This Report Shall Not Be Reproduced Except In Full Without The Expressed Written Approval of The CMTL Supervisor.



This Contract Is Subject To The Terms And Conditions Of Sale Shown On The Order Acknowledgement.  
Ce Contrat est Sujet aux Termes et Conditions de Vente Indiques Sur l'Accuse de Reception de Commande.