

ArcelorMittal Dofasco G.P.
P.O. Box 2460
Hamilton, Ontario
L8N 3J5

TEST REPORT
RAPPORT D'ESSAI

Attention: [NAME]
Fax: [FAX]
Date: 11/17/2019

-Purchase Order/Bon de Commande- -Customer/Client- -Sales Order/Bon de Commande- -Vendor/Vendeur-
AMMEX-DOFASCO-001 002050 HS2 393059001
-Bill of Lading/Connaissance- -Packing Slip/Bordereau de Charge- -Vehicle or Carrier/Vehicule ou Transporteur-
544577 CNRAIL

-Sold To/Vendu A- -Ship To/Expedier A-
ARCELORMITTAL MEXICOS.A. DE C.V. ARCELORMITTAL MEXICOMONTERREY
1G FRANCISCO J'MUGICA 28.2 C.A.V. LIBR. NORESTE
LAZARO CARDENAS, MICHOACAN ESCOBEDO, NUEVO LEON
MEXICO 60950 MEXICO 66050
SACHIN BHATT

-Spec/Norm et Spec- -Material Description/Description du Material-
STANDARD THICKNESS TOLERANCE HOT ROLLED STEEL SHEET
SAE J 403 GRADE 1010 B (JUN2014) COMMERCIAL STEEL
STANDARD UNEXPOSED SURFACE COILS
MATERIAL CERTIFICATION REQUIRED MILL EDGE PLAIN DRY
Code: 44-97

.1345 X 48 X COIL
WEIGHT: 42720 LBS
-Test Methods/Methods d'Essai-
ASTM E1019, E415

HEAT Chemical testing performed by an ISO/IEC 17025 certified laboratory

COULEE	C	Mn	P	S	Si	Cu	Ni	Cr	Sn	Mo	Als	Alt	Cb	V	Ti	Ca	N	B	O
760338	.08	.38	.005	.005	.02	.05	.02	.04	.002	.003	.031	.032	.001	.001	.005	.0001	.0033	.0000	

SERIAL NUMBER LIFT #
NOMBRE DE SERIE FARDEAU
F25601/00 5002741

We Certify That The Material Described Herein Conforms To The Specification Shown On This Document
As shipped from ArcelorMittal Dofasco G.P. as per John Duric - CMTL Supervisor 905-548-7200 x 6960
The Results Relate Only To The Items Tested
This Report Shall Not Be Reproduced Except In Full Without The Expressed Written Approval of The CMTL Supervisor.



This Contract Is Subject To The Terms And Conditions Of Sale Shown On The Order Acknowledgement.
Ce Contrat est Sujet aux Termes et Conditions de Vente Indiques Sur l'Accuse de Reception de Commande.