ArcelorMittal Dofasco G.P.
P.O. Box 2460
Hamilton, Ontario
L8N 3J5

TEST REPORT
RAPPORT D'ESSAI

Attention: [NAME]
Fax: [FAX]
Date: 11/18/2019

-Purchase Order/Bon de Commande-
AMMEX-DOFASCO-001

-Customer/Client-
002050

-Sales Order/Bon de Commande-
HS2 393059001

-Vendor/Vendeur-

-Bill of Lading/Connaissement-
544598

-Packing Slip/Bordereau de Charge-

-Vehicle or Carrier/Vehicule ou Transporteur-
CNRAIL

-Sold To/Vendu A-
ARCELORMITTAL MEXICOS.A. DE C.V
1G FRANCISCO J'MUGICA
LAZARO CARDENAS, MICHOACAN
MEXICO 60950

-Ship To/Expedier A-
ARCELORMITTAL MEXICOMONTERREY
28.2 C.A.V. LIBR. NORESTE
ESCOBEDO, NUEVO LEON
MEXICO 66050
SACHIN BHATT

-Spec/Norm et Spec-
STANDARD THICKNESS TOLERANCE
SAE J 403 GRADE 1010 B (JUN2014)
STANDARD UNEXPOSED SURFACE
MATERIAL CERTIFICATION REQUIRED
Code: 44-97

-Material Description/Description du Material-
HOT ROLLED STEEL SHEET
COMMERCIAL STEEL
COILS
MILL EDGE PLAIN DRY

.1345 X 48 X COIL
WEIGHT: 42640 LBS

-Test Methods/Methods d'Essai-
ASTM E1019, E415

HEAT Chemical testing performed by an ISO/IEC 17025 certified laboratory

COULEE	C	Mn	P	S	Si	Cu	Ni	Cr	Sn	Mo	Als	Alt	Cb	V	Ti	Ca	N	B	O
760347	.10	.36	.007	.004	.02	.05	.02	.05	.002	.004	.033	.033	.001	.001	.005	.001	.0035	.0000	

SERIAL NUMBER	LIFT #
NOMBRE DE SERIE	FARDEAU
F25602/00	5001725

We Certify That The Material Described Herein Conforms To The Specification Shown On This Document
As shipped from ArcelorMittal Dofasco G.P. as per John Duric - CMTL Supervisor 905-548-7200 x 6960
The Results Relate Only To The Items Tested
This Report Shall Not Be Reproduced Except In Full Without The Expressed Written Approval of The CMTL Supervisor.

This Contract Is Subject To The Terms And Conditions Of Sale Shown On The Order Acknowledgement.
Ce Contrat est Sujet aux Termes et Conditions de Vente Indiques Sur l'Accuse de Reception de Commande.