

# AM/NS Calvert LLC

1 AM/NS Way  
Calvert, Al. 36513 USA



## Mill Certificate

CUSTOMER ORIGINAL

|  |                                  |  |                    |  |
|--|----------------------------------|--|--------------------|--|
| Order - Item<br>178405-160   | Certificate Number<br>1188438540 | Delivery No<br>82277888-10   | Date<br>08/16/2019 | Page<br>1 of 1   |
| Customer No: 14552   |                                  | Cust PO: AMMEX00943  |                    |  |
| Customer Part No: 16-  |                                  |  |                    |  |
| Customer Sold to:<br>ArcelorMittal Mexico<br>SA de CV<br>Francisco J Mugica 1 G Centro<br>60950 LAZARO CARDENAS<br>MEXICO                                |                                  | Customer Ship to:<br>ArcelorMittal Mexico SA de CV<br>Administracion Portuaria Integral<br>Edificio API Tampico S/N<br>89000 TAMPICO<br>MEXICO |                    | Contact - Stan Bevans<br>AM/NS Calvert LLC<br>1 AM/NS Way<br>CALVERT AL 36513<br>USA<br>Email: Stanley.Bevans@ArcelorMittal.com<br>Ph : 1-251-289-3000 |
| Steel Grade / Customer Specification<br>Hot Roll Black Coil Conv to A36 / 0.2500 " X 48.0000 " ACCORDING TO A1018 {Hvy 0.230"(6)-1"(25.4)}-Hot Roll Base |                                  |  |                    |  |
| Type of Product/Surface<br>Hot Roll Black Coil Unexposed IDS UNEXPOSED   |                                  |  |                    |  |

|                                     |                        |                     |                     |                     |                       |        |      |       |       |        |
|-------------------------------------|------------------------|---------------------|---------------------|---------------------|-----------------------|--------|------|-------|-------|--------|
| TEST METHOD                         | Melted in Mexico       |                     | Manufactured in USA |                     |                       |        |      |       |       |        |
| ASTM                                | Country of origin: USA |                     |                     |                     |                       |        |      |       |       |        |
| MATERIAL DESCRIPTION                |                        |                     |                     | Weight<br>Net<br>LB | Weight<br>Gross<br>LB |        |      |       |       |        |
|                                     | ORDERED                | Heat<br>No.         | Coil<br>No.         |                     |                       |        |      |       |       |        |
| (mm)                                | 6.350                  | 1940399             | 1188438540          | 46,341.000          | 46,341.000            |        |      |       |       |        |
| (in)                                | 0.2500                 |                     |                     |                     |                       |        |      |       |       |        |
| CHEMICAL COMPOSITION OF THE LADLE * |                        |                     |                     |                     |                       |        |      |       |       |        |
| Heat<br>No.                         | C                      | Si                  | Mn                  | P                   | S                     | Al     | Cr   | Cu    | Mo    | N      |
| 1940399                             | 0.2160                 | 0.02                | 0.42                | 0.011               | 0.004                 | 0.046  | 0.01 | 0.003 | 0.005 | 0.0037 |
|                                     | Ni                     | Nb                  | Ti                  | B                   | V                     | Ca     |      |       |       |        |
|                                     | 0.020                  | 0.002               | 0.001               | 0.0000              | 0.002                 | 0.0017 |      |       |       |        |
| TENSILE TEST                        |                        |                     |                     |                     |                       |        |      |       |       |        |
| Test<br>Direction                   | Yield<br>Strength      | Tensile<br>Strength | % Total<br>Elong.   |                     |                       |        |      |       |       |        |
| T                                   | 48 ksi                 | 67 ksi              | 41                  |                     |                       |        |      |       |       |        |

This is not a NAFTA or any other FTA certificate of origin  
AM/NS Calvert LLC certify that the material herein described has been manufactured, sampled, tested and inspected in accordance with the contract requirements and is fully in compliance.

\* - This test is not covered by our current A2LA accreditation

Yasunori Iwasa  
Quality Management Director  
AM/NS Calvert