MATERIAL TEST CERTIFICATE

PHYSICALS MATERIAL: ASTM A216 GR WCB YIELD TENSILE CHEMICALS %EL %RA BHN KSI Ni. Mo. KSI Cr. Cu. HEAT NO. Mn. 147 0.06 0.06 0.03 0.003 0.023 0.58 0.06 C50936 0.92 0.023 0.20 0.05 0.03 28 0.44 0.02 0.023 0.06 0.005 0.24 0.62 C61856 0.028 44 38 0.41 0.04 0.04 0.04 0.03 0.005 0.92 0.024 0.021 C62131 0.24 0.04 0.06 0.02 0.002 0.47 0.05 C62892 0.21 0.62 0.028 0.020 Our letters are for the exclusive use of the client to whom they 1990 PRESSURE TEST **API 598** are addressed. The use of our name must receive our written approval. Our letters and reports apply only to the sample

AES FIG. NO.: 02GA06RHA11

DWHEEL OPERATED

2" 600# CS RF GATE VALVE

AES CONTROL NO.: 3351

CUSTOMER P.O.: 98/004

QUANTITY: 2 OF 10

"STANDARD TRIM

ITEM NO.: 24

IDENTIFICATION NOS.

SIZE & DESCRIPTION

AMERICAN ENERGY SERVICES

P. O. BOX 34356

HOUSTON, TEXAS 77234

PHONE: (713) 928-5311

FAX (713) 928-6479

CUSTOMER

FERRETERA ANAHUAC S.A. DE C.V.

C/O OSCAR FERNANDEX OF TX (FASA)

14215 TRANSPORTATION AVE.

LAREDO, TEXAS USA

33171, 33173

psi	-	e service en la lace			We delike USSSETE TO	11 11
SHELL	SEAT	Α	SEAT	В	BACK S	SEAT
HYDRO	HYDRO	AIR	HYDRO	AIR	HYDRO	AIR
2225		80		80		80

SECONDS			
60	60	60	60

DIMENSIONS CONFORM TO ASME/ANSI B16.34

are addressed. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested an/or inspected, and are not necessarily indicative of the qualities of apparently identical or similar products. We certify the materials meet the referenced specifications as reported on the material manufacturer's test certificates which are maintained in our files. The information contained in this report is true and correct to the best of my knowledge. This report is issued by the Quality Assurance Department which is independent of the Manufacturing or Processing Department. It conforms to Din Standard 50049-3.1B and to ISO standard 10474-3.1B.

January 14, 1998

DATE:

QUALITY ASSURANCE