Material Test Report

Heat Code; xPX

Coffer Corp.

An AFGlobal Company

13770 Industrial Rd. Houston, TX 77015

13770 Industrial Rd. Houston, 1X 77015 Sales: (713) 868-4421 Fax: (713) 455-8366

COFFER® an AFFIRSDA Company

00012015 PO: 261

ISO 9001:2008 Certified

Sales

Sales Order: 138418

Line: 2

11811 NORTH FRWY STE 500

Item Code: 0303600100-0020F
Item Desc: FLG 06.00 0300 BL RF A105

Qty Shipped: 10

NHT COFFR

Houston, TX 77060

PLESA STEEL INC.

Supplier: ASW-STEEL

Supplier Heat: 76821

Spec: ASTM A105/A105M-(13)/ASME SA 105/SA 105M-(13) Section II Part A

Mn Manganese 1.06 ✓ 7439-96-5 Mo Molybdenum 0.02 P Phosphorous 0.010 V Vanadium 0.001 S Sulphur 0.001 Cb Columbium 0.004 Si Silicon 0.21 C.E. 0.40 Cu Copper 0.23 ✓ 7440-50-8 CuNiCrMoV 0.387	Elei	ment (%wt)	Ladle	Product	EPCRA	CAS#	Element	(%wt)	Ladle	Product	EPCRA	CAS#
P Phosphorous 0.010 V Vanadium 0.001 S Sulphur 0.001 Cb Columbium 0.004 Si Silicon 0.21 C.E. 0.40 Cu Copper 0.23 ✓ 7440-50-8 CuNiCxMoV 0.387	С	Carbon	0.19				Cr Chrom	i.um	0.08		√	7440-47-3
S Sulphur 0.001 Cb Columbium 0.004 Si Silicon 0.21 C.E. 0.40 Cu Copper 0.23 ✓ 7440-50-8 CuNiCrMoV 0.387	Mn	Manganese	1.06		/	7439-96-5	Mo Molyb	denum	0.02			
Si Silicon 0.21 C.E. 0.40 Cu Copper 0.23 ✓ 7440-50-8 CuNiCrMoV 0.387	P	Phosphorous	0.010				V Vanad	ium	0.001			
Cu Copper 0.23 ✓ 7440-50-8 CuNiCrMoV 0.387	S	Sulphur	0.001				Cb Colum	bium	0.004			
	Si	Silicon	0.21				C.E.		0.40			
Ni Nickel 0.06 / 2440-02-0 CrMo 0.096	Cu	Copper	0.23		✓	7440-50-8	CuNiCrMo'	V	0.387			
7440-02-0 , CINO 0.030	Ni	Nickel	0.06		✓	7440-02-0	CrMo		0.096			
							i					

Mechanical '	Testing	Other		
Test Lab	AFG	Country of Melt	CANADA	
Test Bar Size	Sacrificial Piece	EF	Y	
HBW	163 - 163	Fully Killed	Y	
Elg (%)	25			
RA (%)	43	i i		
Tensile Specimen Size (in)	.491	1		
Tensile (ksi)	77.5	1		
Yield (ksi)	45.7			
Gauge Length	2			

Product compliant with NACE MR0175 / ISO 15156 latest edition and flange dimensions to ASME B16.5

* No Weld repair performed.

* Ladle Chemical Analysis results are reported from the raw material suppliers MTR.

* Forgings are capable of passing hydrostatic test compatible with the appropriate rating.

* Elongation taken from a round specimen.

* Yield strength was determined using the .2% offset method.

* All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing.

* When reported on MTR: Tensile Testing Per ASTM E8; Brinell Hardness Per ASTM E10; Charpy Testing Per ASTM E23

* AF Global manufactures materials according to a certified Quality Management System conforming to ISO 9001:2008 and PED 97/23/EC, Annex 1, Section 4.3

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Pfanning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1988) and 40 C.F.R. Part 372. Potentially reportable chemicals are inclosted with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release inventory Report under EPCRA Section 313.

Certification No.:

1123974

Certification Date:

8/6/2014

Issued By:

Juan Diaz

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b

Rina Sane - Metallurgical Lab Manager