

Material Test Report

Heat Code: C-0441

An Ameri-Forge Group Company 13770 Industrial Rd. Houston, TX 77015

ISO 9001:2008 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA DE CV AV. VALLE DE LAS ALAMEDAS 66-0

54940 TULTITLAN, EDO, MEX

PO: 10492 Sales Order: 95070 Line: 14 Item Code: 0151916102-0021F Qty Shipped: 20

Item Desc: FLG 16.00 0150 WN RF XH

Supplier: MF RINGS Supplier Heat: C-0441

Spec: ASTM A105/A105N-(10)/ASME SA 105/SA 105N-(08a) Section II Part A - Normalized

| Ele | ment (%wt) | Ladle | Product | EPCR | A CAS# | Eler | ment (%wt) | Ladle | Product | EPCR | A CAS# |
|-----|-------------|-------|---------|------|-----------|------|------------|-------|---------|------|-----------|
| C | Carbon | 0.21 | | | | Ni | Nickel | 0.01 | | 1 | 7440-02-0 |
| Mn | Manganese | 0.96 | | 1 | 7439-96-5 | Cr | Chromium | 0.02 | | 1 | 7440-47-3 |
| P | Phosphorous | 0.018 | | | | Mo | Molybdenum | 0.008 | | | |
| S | Sulphur | 0.013 | | | | : v | Vanadium | 0.008 | | | |
| Si | Silicon | 0.23 | | | | Cb | Columbium | 0.006 | | | |
| Cu | Copper | 0.01 | | 1 | 7440-50-8 | C.E | | 0.41 | | | |

| esting | : | Heat Treat | |
|-------------------|---|--|--|
| MF RINGS | Norm. Temp. (F) | | 1652 |
| SACRIFICIAL PIECE | Norm. (Hrs) | | 4 |
| 156 - 156 | Norm. Cooling Type | | AIR |
| 30.4 | • | | |
| 58.5 | | Other | |
| 0.498 | VD | | Y |
| 75.2 | EF | | Y |
| 46.9 | | | |
| 2 | | | |
| | | | |
| | | | |
| | : | | |
| | | | |
| | | | |
| | : | | |
| | | | |
| | • | | |
| | | | |
| | • | | |
| | MF RINGS SACRIFICIAL PIECE 156 - 156 30.4 58.5 0.498 75.2 46.9 | MF RINGS Norm. Temp. (F) SACRIFICIAL PIECE Norm. (Hrs) 156 - 156 Norm. Cooling Type 30.4 58.5 0.498 VD 75.2 46.9 | MF RINGS Norm. Temp. (F) SACRIFICIAL PIECE Norm. (Hrs) 156 - 156 Norm. Cooling Type 30.4 58.5 Other 0.498 VD 75.2 46.9 |

Product compliant with NACE MR0175 and NACE MR0103 latest edition and dimensions to ANSI B16.5. No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method. No welding performed.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

207635

Certification Date:

5/11/2011

Nicholas Tepovich - Metallurgic Lab Manager

Nielales Teparel