



Material Test Report

Heat Code: UCB

An Ameri-Forge Group Company

13770 Industrial Rd. Houston, TX 77015

ISO 9001:2008 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

| | | | |
|--|---------------------------------|---------------------|------------------------|
| PLESA STEEL INC. 5100 WESTHEIMER ROAD SUITE 200 Houston, TX 77056 | PO: 82 | Sales Order: 122004 | Line: 1 |
| | Item Code: 0302400100-0020F | | Qty Shipped: 30 |
| | Item Desc: FLG 04.00 0300 SO RF | | |
| | Supplier: CMC | | Supplier Heat: 3032598 |

Spec: ASTM A105/A105M-(12)/ASME SA 105/SA 105M-(08a) Section II Part A

| Element | (%wt) | Ladle | Product | EPCRA | CAS# | Element | (%wt) | Ladle | Product | EPCRA | CAS# |
|---------|-------------|-------|---------|-------|-----------|----------|------------|-------|---------|-------|-----------|
| C | Carbon | 0.19 | | | | Cr | Chromium | 0.07 | | ✓ | 7440-47-3 |
| Mn | Manganese | 1.04 | | ✓ | 7439-96-5 | Mo | Molybdenum | 0.03 | | | |
| P | Phosphorous | 0.011 | | | | V | Vanadium | 0.002 | | | |
| S | Sulphur | 0.013 | | | | Cb | Columbium | 0.003 | | | |
| Si | Silicon | 0.25 | | | | C.E. | | 0.41 | | | |
| Cu | Copper | 0.28 | | ✓ | 7440-50-8 | CuNiCrMo | | 0.488 | | | |
| Ni | Nickel | 0.11 | | ✓ | 7440-02-0 | CrMo | | 0.098 | | | |

| Mechanical Testing | | | | Other | | | |
|----------------------------|--|-------------------|--|--------------------|--|-----------|--|
| Test Lab | | AFG | | :MILL | | CMC-TEXAS | |
| Test Bar Size | | Sacrificial Piece | | :MHC | | 3032598 | |
| HBW | | 163 - 163 | | :Country of Origin | | USA | |
| Elg (%) | | 32 | | :EF | | Y | |
| RA (%) | | 60 | | | | | |
| Tensile Specimen Size (in) | | ,498 | | | | | |
| Tensile (ksi) | | 81.4 | | | | | |
| Yield (ksi) | | 49.5 | | | | | |
| Gauge Length | | 2 | | | | | |

No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. Yield strength was determined using the .2% offset method. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Made in USA.
 No weld repair performed on this product.
 Product compliant with NACE MR0175 / ISO 15156 latest edition and dimensions to ANSI 816.5 - 2009
 Tensile Testing Per ASTM E8; Brinell Hardness Per ASTM E10
 Forged in USA

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III) of the Superfund Amendments and Reauthorization Act of 1986 and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 263702
 Certification Date: 3/25/2013

M. Hingwe
 Mandar Hingwe - Dir. of Quality and Metallurgy