

Material Test Report

An Ameri-Forge Group Company 13770 Industrial Rd. Houston, TX 77015

ISO 9001:2000 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA DE CV AV. VALLE DE LAS

54940 TULTITLAN, EDO, MEX

Item Code:

0152300100-0020F

Sales Order: 75369 Line: 3

ALAMEDAS 66-0

Item Desc: FLG 03.00 0150 SO RF

Qty Shipped: 6

Supplier: CMC

PO: 8379

Supplier Heat: 3016000

Spec: ASTM A105/A105M-(10)/ASME SA 105/SA 105M-(08a) Section II Part A

| Elem | ent (%wt) | Ladle | Product | EPCRA CAS | Elemen | t (%wt) | Ladle | Product | EPCRA | CAS# |
|------|-------------|-------|---------|-----------------|-------------------|-----------|-------|---------|-------|----------|
| С | Carbon | 0.21 | | | Cr c | romium | 0.07 | | √ 7 | 440-47-3 |
| Mn | Manganese | 1.05 | | √ 7439-9 | -5 : Mo Mo | olybdenum | 0.01 | | | |
| P | Phosphorous | 0.009 | | | V Va | anadium | 0.002 | | | |
| S | Sulphur | 0.017 | | | Cb co | olumbium | 0.001 | | | |
| Si | Silicon | 0.23 | | | C.E. | | 0.42 | | | |
| Cu | Copper | 0.22 | | ✓ 7440-5 | -8 CuNiCr | :Mo | 0.373 | | | |
| Ni | Nickel | 0.07 | | ✓ 7440-0 | -0 CrMo | | 0.083 | | | |
| | | | | | | | | | | |
| | | | | | : | | | | | |

| Mechanical To | esting | C |)ther |
|----------------------------|------------|-------------------|-----------|
| Test Lab | AFG | MILL | CMC-TEXAS |
| Test Bar Size | Test Piece | MHC | 3016000 |
| HBW | 170 - 170 | Country of Origin | USA |
| Elg (%) | 30.0 | EF | Y |
| RA (%) | 60.0 | Fully Killed | Y |
| Tensile Specimen Size (in) | .248 | | |
| Tensile (ksi) | 81.9 | | |
| Yield (ksi) | 49.7 | | |
| Gauge Length | 1 | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| ` | | | |
| | | | |
| | | <u>:</u> | |

Product compliant with NACE MR0175, latest edition and dimensions to ASME B16.5 Product compliant with and meets all requirements of ASTM A105/ASME SA105, latest edition. No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method. No weld repair performed on this product. Product compliant with NACE MR0103, latest edition.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthonization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

184962

Certification Date:

6/24/2010

Nicholas Tepovich - Metallurgic Lab Manager

Violadas Lepane