

ALAMEDAS 66-0

PLESA ANAHUAC Y CIAS

SA DE CV AV. VALLE DE LAS

Material Test Report

Heat Code: HVU

An Ameri-Forge Group Company 13770 Industrial Rd. Houston, TX 77015 Sales: (713) 868-4421 Fax: (713) 455-8366

Qty Shipped: 10

ISO 9001:2008 Certified

Sales Order: 90421 Line: 3

Item Code: 0153600100-0020F

Item Desc: FLG 06.00 0150 BL RF

54940 TULTITLAN, EDO, MEX Supplier: CMC Supplier Heat: 3018265

Spec: ASTM A105/A105M-(10)/ASME SA 105/SA 105M-(08a) Section II Part A

PO: 9545

Eler	nent (%wt)	Ladie	Product	EPCR	A CAS#	Element	(%wt)	Ladie	Product	EPCRA	CAS#
С	Carbon	0.20				Cr Chr	omium	0.08		V 7	440-47-3
Mn	Manganese	1.07		✓	7439-96-5	Mo Mol	ybdenum	0.03			
P	Phosphorous	800.0				V Van	adium	0.002			
S	Sulphur	0.020				Cb Col	umbium	0.001			
Si	Silicon	0.22				C.E.		0.422			
Cu	Copper	0.24		✓	7440-50-8	CuNiCrM	0	0.438			
Ni	Nickel	0.09		✓	7440-02-0	CrMo		0.118			
						•					
						:					

Test Lab AFG MILL Test Bar Size Test Piece MEC HBW 156 - 156 EF Elg (%) 33.0 Fully Killed RA (%) 64.0 Fully Killed Tensile Specimen Size (in) 0.251 Tensile (ksi) Tensile (ksi) 79.5 Yield (ksi) Gauge Length 1.0 Tensile (ksi)	CMC-TEXAS 3018265 Y Y
HBW 156 - 156 EF Elg (%) 33.0 Fully Killed RA (%) 64.0 Tensile Specimen Size (in) 0.251 Tensile (ksi) 79.5 Yield (ksi) 47.9	¥
Elg (%) 33.0 Fully Killed RA (%) 64.0 Tensile Specimen Size (in) 0.251 Tensile (ksi) 79.5 Yield (ksi) 47.9	
RA (%) 64.0 Fensile Specimen Size (in) 0.251 Fensile (ksi) 79.5 Wield (ksi) 47.9	¥
Tensile Specimen Size (in) 0.251 Tensile (ksi) 79.5 Yield (ksi) 47.9	
Tensile (ksi) 79.5 Yield (ksi) 47.9	
Yield (ksi) 47.9	
· · · · · · · · · · · · · · · · · · ·	
Gauge Length 1.0	

No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method. No weld repair performed on this product.

Product compliant with and meets all requirements of ASTM A105 and with dimensions to ASME B16.5 Product compliant with NACE MR0175, latest edition

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release inventory Report under EPCRA Section 313,

Certification No.:

196504

Certification Date:

12/16/2010

Nicholas Tepovich - Metallurgic Lab Manager

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b