

Material Test Report

Heat Code: JSW

An Ameri-Forge Group Company 13770 Industrial Rd. Houston, TX 77015

ISO 9001:2008 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA DE CV AV. VALLE DE LAS

Item Code: 0152600100-0020F

Sales Order: 99187 Line: 3

ALAMEDAS 66-0

Item Desc: FLG 06.00 0150 SO RF

Qty Shipped: 50

54940 TULTITLAN, EDO, MEX

Supplier: CMC

Supplier Heat: 3023959

Spec: ASTM A105/A105M-(10)/ASME SA 105/SA 105M-(08a) Section II Part A

PO: 11073

Mn Manganese 0.99 ✓ 7439-96-5 Mo Molybdenum 0.02 P Phosphorous 0.011 V Vanadium 0.004 S Sulphur 0.014 Cb Columbium 0.001 Si Silicon 0.22 C.E. 0.40 Cu Copper 0.24 ✓ 7440-50-8 CuNiCrMo 0.435	Elen	nent (%wt)	Ladle	Product	EPCR/	CAS#	Element	(%wt)	Ladle	Product	EPCRA	ÇAS#
P Phosphorous 0.011 V Vanadium 0.004 S Sulphur 0.014 Cb columbium 0.001 Si Silicon 0.22 C.E. 0.40 Cu Copper 0.24 ✓ 7440-50-8 CuNiCrMo 0.435	С	Carbon	0.19				Cr Chrom	ium	0.09		√ 7	440-47-3
S Sulphur 0.014 Cb Columbium 0.001 Si Silicon 0.22 C.E. 0.40 Cu Copper 0.24 ✓ 7440-50-8 CuNiCrMo 0.435	Mn	Manganese	0.99		✓ .	7439-96-5	Mo Molyb	denum	0.02			
Si Silicon 0.22 C.E. 0.40 Cu Copper 0.24 ✓ 7440-50-8 CuNiCrMo 0.435	P	Phosphorous	0.011				V Vanad	ium	0.004			
Cu Copper 0.24 ✓ 7440-50-8 CuNiCrMo 0.435	S	Sulphur	0.014				Cb Colum	bium	0.001			
	Si	Silicon	0.22				C.E.		0.40			
Ni Nickei 0.08 ✓ 7440-02-0 :CrMo 0.115	Cu	Copper	0.24		✓ '	7440-50-8	CuNiCrMo		0.435			
	Ni	Nickel	0.08		✓	7440-02-0	CrMo		0.115			
							:					

		· · · · · · · · · · · · · · · · · · ·				
Mechanical To	esting	Other				
Test Lab	AFG	MILL		CMC-TEXAS		
Test Bar Size	Sacrificail Piece	мнс		3023959		
HBW	179 - 179	EF		Y		
Elg (%)	28.0	•				
RA (%)	54.0	:				
Tensile Specimen Size (in)	.504	•				
Tensile (ksi)	82.0					
Yield (ksi)	50.1	•				
Gauge Length	2	•				
		•				
		•				
		<u>:</u>				
		:				
		:				
		:				

No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method. No weld repair performed on this product.

Product compliant with NACE MR0175, latest edition and dimensions to ASME B16.5

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title II) of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

216581

Certification Date:

8/26/2011

Nicholas Tepovich - Metallurgic Lab Manager