



Material Test Report

Heat Code: YZV

An Ameri-Forge Group Company
13770 Industrial Rd., Houston, TX 77015

ISO 9001:2000 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

| | | | |
|---|--|-----------------------|-----------------|
| PLESA ANAHUAC Y CIAS | PO: 3815 | Sales Order: 62636 | Line: 6 |
| SA DE CV AV. VALLE DE LAS | Item Code: 0302800100-0020f | | Qty Shipped: 25 |
| ALAMEDAS 66-0 | Item Desc: FLG 08.00 0300 SO RF A105 NHT COFFR | | |
| 54940 TULTITLAN, EDO MEX | Supplier: CMC | Supplier Heat: 257492 | |
| Spec: ASTM A 105/A 105M-03/ASME SA 105/SA 105M-04, Melt Practice EF | | | |

| Element | (%wt) | Ladle | Product | EPCRA | CAS# | Element | (%wt) | Ladle | Product | EPCRA | CAS# |
|---------|-------------|-------|---------|-------|-----------|----------|------------|-------|---------|-------|-----------|
| C | Carbon | 0.20 | | | | Cr | Chromium | 0.14 | | ✓ | 7440-47-3 |
| Mn | Manganese | 0.91 | | ✓ | 7439-96-5 | Mo | Molybdenum | 0.024 | | | |
| P | Phosphorous | 0.011 | | | | V | Vanadium | 0.001 | | | |
| S | Sulphur | 0.014 | | | | Cb | Columbium | 0.002 | | | |
| Si | Silicon | 0.19 | | | | C.E. | | 0.411 | | | |
| Cu | Copper | 0.31 | | ✓ | 7440-50-8 | CuNiCrMo | | 0.56 | | | |
| Ni | Nickel | 0.09 | | ✓ | 7440-02-0 | CrMo | | 0.16 | | | |

| Mechanical | | | | Other | | | |
|----------------------------|--|-------------------|--|-------------------|--|----------|--|
| Test Bar Size | | SACRIFICIAL PIECE | | Country of Origin | | USA (US) | |
| HBW | | 167-167 | | EF | | Y | |
| Elg (%) | | 34.0 | | | | | |
| RA (%) | | 63.0 | | | | | |
| Tensile Specimen Size (in) | | 0.502 | | | | | |
| Tensile (ksi) | | 78.4 | | | | | |
| Yield (ksi) | | 45.6 | | | | | |
| Gauge Length | | 2.00 | | | | | |

Material on this report is certified to NACE MR-01-75 and DIMS. to ANSI B16.5
Product compliant with NACE MRO175, latest edition.

Product compliant with and meets all requirements of ASTM A105/ASME SA105-05.
No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 131287
Certification Date: 12/11/2007

Kevin Papich - Tech. Svcs. Manager