

Material Test Report

Heat Code: CGS

An Ameri-Forge Group Company 13770 Industrial Rd., Houston, TX 77015

ISO 9001:2000 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA *DE GV AV. VALLE DE LAS

Item Code: 0151600101-0020F

Sales Order: 66234 Line: 3

P Qty Shipped: 96

ALAMEDAS 66-0

Item Desc: FLG 06.00 0150 WN RF STD A105

05 NHT COFFR

54940 TULTITLAN, EDO MEX

Supplier: CMC

PO: 4970

Supplier Heat: 3004251

Spec: ASME SA-105/SA-105M 2004 Section II/ASTM A105/A105M-03

Mn Manganese 0.92	Elen	nent	(%wt)	Ladle	Product	EPCRA	CAS#	Element	(%wt)	Ladie	Product	EPCRA	CAS#
P Phosphorous 0.007 V Vanadium 0.001 S Sulphur 0.015 Cb Columbium 0.001 Si Silicon 0.18 C.E. 0.379 Cu Capper 0.20 ✓ 7440-50-8 CuNiCrMo 0.35	C	Carbon		0.19				Cr Chromium		0.08		V 7	7440-47-
S Sulphur 0.015 . Cb Columbium 0.001 Si Silicon 0.18 C.E. 0.379 Cu Capper 0.20 ✓ 7440-50-8 CuNiCrMo 0.35	Mn	Mangar	ese	0.92		1 7	439-96-5	Mo Molyho	denum	0.012			
Si Silicon 0.18 C.E. 0.379 Cu Copper 0.20 ✓ 7440-50-8 CUNICrMo 0.35	P	Phosph	orous	0.007				V Vanada	ium	0.001			
Cu copper 0.20	S	Sulphi	r	0.015	٠.			Cb Columb	oium	0.001			
Cu copper	Si	Silico	n	0.18				C.E.		0.379			
0.00	Cu	Coppe		0.20		/ 7	7440-50-8	CuNiCrMo		0.35			
Ni Nickel 0.06 7 7440-02-0 CEMO 0.05	Ni	Nicke		0.06		1 7	7440-02-0	CrMo		0.09			
	•												

Mechanica		Other				
Test Lab	ĄFG	Country of Origin	USA (US)			
Test Bar Size	SACRIFICIAL PIECE	EF	Y			
нви	156-156					
Elg (%)	39.0					
RA (%)	69.0					
Tensile Specimen Size (in)	0.250					
Tensile (ksi)	75.7					
Yield (ksi)	44.2					
Gauge Length	1.00	At a second of				
4						
2						
	•	· · · · · · · · · · · · · · · · · · ·				
	· · · · · · · · · · · · · · · · · · ·					
		May.				

Product compliant with NACE MRO175, latest edition.

Product compliant with and meets all requirements of ASTM A105/ASME SA105, latest edition.

No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

148153

Certification Date:

8/20/2008

This report is issued in comphance with the requirements of EN10204 3.1 / ISO 10474 3 1.b

Puneet Saggar - Plant Metallurgist