

Material Test Report

Heat Code: CVK

An Ameri-Forge Group Company 13770 Industrial Rd., Houston, TX 77015

ISO 9001:2000 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA DE CV AV. VALLE DE LAS

Item Code: 0153912100-0020F

Line: 22 Sales Order: 67635

ALAMEDAS 66-0

Qty Shipped: 15

A105

Item Desc: FLG 12.00 0150 BL RF

NHT COFFR

54940 TULTITLAN, EDO MEX

Supplier Heat: J85041 Supplier: CMC

Spec: ASTM A 105/A 105M-(05)/ASME SA 105/SA 105M-(08a) Section II Part A

PO: 5526

Mn Manganese 0.72	Elemen	t (%wt)	Ladle	Product	EPCRA CAS#	Element (%wt)	Ladle	Product	EPCRA CAS#
P Phosphorous 0.010 V Vanadium 0.002 S Sulphur 0.029 Cb Columbium 0.001 Si Silicon 0.20 C.E. 0.378 Cu Copper 0.31 ✓ 7440-50-8 CuNiCrMo 0.63	C Ca	arbon	0.19			Cr Chromium	0.16		√ 7440-47-3
S Sulphur 0.029 Cb Columbium 0.001 Si Silicon 0.20 C.E. 0.378 Cu Copper 0.31 ✓ 7440-50-8 CuNiCrMo 0.63	Mn Ma	anganese	0.72		√ 7439-96-5	Mo Molybdenum	0.034		
Si Silicon 0.20 C.E. 0.378 Cu Copper 0.31 ✓ 7440-50-8 CuNiCrMo 0.63	P Ph	nosphorous	0.010			V Vanadium	0.002		
Cu Copper 0.31 ✓ 7440-50-8 CuNiCrMo 0.63	S Su	ılphur	0.029			Cb Columbium	0.001		
- Control of the cont	Si si	ilicon	0.20			C.E.	0.378		
Ni Nickel 0.13 ✓ 7440-02-0 :CrMo 0.19	Cu Co	opper	0.31		✓ 7440-50-8	CuNiCrMo	0.63		
	Ni Ni	ickel	0.13		√ 7440-02-0	CrMo	0.19		

Mechanical		<u>:</u>	Other
Test Lab	AFG	EF	Y
Test Bar Size	SACRIFICIAL PIECE		
HBW	149-149	:	
Elg (%)	34.0		
RA (%)	60.0		
Tensile Specimen Size (in)	0.498		
Tensile (ksi)	73.5		
Yield (ksi)	40.7		
Gauge Length	2.00		
		:	
		:	

Product compliant with NACE MR0175 / ISO 15156, latest edition and dimensions to ANSI B16.5 Product compliant with and meets all requirements of ASTM A105/ASME SA105, latest edition.

No Weld repair performed. Chemical Analysis results shown are actual. Forgings are capable of passing hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

156070

Certification Date:

12/17/2008

Nicholas Tepovich - Metallurgic Lab Manager

Vieleles Lepare

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b