

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

API 598 - VALVE INSPECTION AND TESTING
 API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
 ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
 ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
 MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
 API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
 ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
 API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AC061A12MAA**
 (Código)
 Description **6" Fig. 5202 F 3HF WCB, API TRIM No.12 7900000**
 Descripción **CAST STEEL GATE VALVE**
(VALVULA COMPUERTA DE ACERO FUNDIDO)


MANUFACTURED TO MEET NACE MR-01-75-2003 REQUIREMENTS AND LOW FUGITIVE EMISSIONS CONTROL
 (VALVULA SERVICIO NACE MR-01-75 *Y CONTROL DE EMISIONES FUGITIVAS 50 PPM'S)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)				COMPOSICIÓN QUIMICA (%)									TENS	YIELD	ELG	RED	BHN
--------------------------	--	--	--	-------------------------	--	--	--	--	--	--	--	--	------	-------	-----	-----	-----

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BONNET BONETE	WH23380	ASTM A-216/WCB	0.196	0.885	0.027	0.016	0.420	0.007	0.017	0.032	0.137	0.001		76.41	43.35	32	52	155
BODY CUERPO	WH14851	ASTM A-216/WCB	0.192	0.850	0.030	0.018	0.430	0.033	0.047	0.018	0.005	0.001		75.83	46.98	33	42	160
WEDGE DISCO	D3560	ASTM A-216/WCB	0.210	0.760	0.024	0.028	0.410	0.030	0.079	0.016	0.085	0.004	0.000	76.85	45.96	24	47	173


Plesa Anáhuac
COPIA CONTROLADA

FAC10-21 REV "2"

 CERTIFICADO POR:
 ASEGURAMIENTO DE CALIDAD

 CERTIFIED BY:
 QUALITY ASSURANCE


 Sandra Ruiz



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepoztollan, Estado de México C.P. 54600

(Numero) Number
 (Fecha) Date

1049/2009
 14/05/2009

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)
 ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598 - VALVE INSPECTION AND TESTING
 API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
 ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
 ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
 MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
 API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
 ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
 API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **BCSB076E12AAB790000C**
 (Código) **3/4" Fig. 950 S 3HF A105, API TRIM No.12 790000C**
 Description **FORGED STEEL GATE VALVE**
 Descripción **(VALVULA COMPUERTA DE ACERO FORJADO)**

MANUFACTURED TO MEET NACE MR-01-75-2003 REQUIREMENTS AND LOW FUGITIVE EMISSIONS CONTROL
 (VALVULA SERVICIO NACE MR-01-75 *Y CONTROL DE EMISIONES FUGITIVAS 50 PPM'S)


PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2970	2970	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) 13248P Item(Partida) 1
 Qty(Cantidad) 5

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%) COMPOSICIÓN QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS	YIELD	ELG	RED	BHN
														KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BODY CUERPO	CAX	ASTM A-105N	0.220	0.720	0.022	0.008	0.270	0.050	0.030	0.020	0.050	0.000	0.000	79.31	52.92	35	54	170
BODY CUERPO	CCL	ASTM A-105N	0.210	0.780	0.019	0.008	0.270	0.040	0.020	0.030	0.070	0.000	0.000	79.02	55.10	37	54	170
YOKE YUGO	CCL	ASTM A-105N	0.210	0.780	0.019	0.008	0.270	0.040	0.020	0.030	0.070	0.000	0.000	79.02	55.10	37	54	170



[Signature]
JESSICA GARCIA

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD
 CERTIFIED BY: QUALITY ASSURANCE

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)
ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. BCSB076E12AAB830000C
(Código)
Description 3/4" Fig. 950 S 3HF A105, API TRIM No.12 830000C
Descripción FORGED STEEL GATE VALVE
(VALVULA COMPUERTA DE ACERO FORJADO)

VALVE WITH LOW EMISSION CONTROL (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)


PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2970	2970	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) 09134P Item(Partida) 1
Qty(Cantidad) 50

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%) **COMPOSICIÓN QUIMICA (%)**

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)										MECHANICAL TESTS (PROP. MECANICAS)					
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BODY CUERPO	CAX	ASTM A-105N	0.220	0.720	0.022	0.008	0.270	0.050	0.030	0.020	0.050	0.000	0.000	79.31	52.92	35	54	170
BODY CUERPO	CCL	ASTM A-105N	0.210	0.780	0.019	0.008	0.270	0.040	0.020	0.030	0.070	0.000	0.000	79.02	55.10	37	54	170
YOKE YUGO	CCL	ASTM A-105N	0.210	0.780	0.019	0.008	0.270	0.040	0.020	0.030	0.070	0.000	0.000	79.02	55.10	37	54	170
YOKE YUGO	CAX	ASTM A-105N	0.220	0.720	0.022	0.008	0.270	0.050	0.030	0.020	0.050	0.000	0.000	79.31	52.92	35	54	170




JESSICA GARCIA

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRUBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. BCSB056E12AAB
(Código)
Description 1/2" Fig. 950 S 3HF A105, API TRIM No.12 830000C
Descripción FORGED STEEL GATE VALVE
 (VALVULA COMPUERTA DE ACERO FORJADO)
 VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	2970	2970	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

Invoice(Factura) 90538 Item(Partida) I
Qty(Cantidad) 150

MECHANICAL TESTS (PROP. MECANICAS)

		CHEMICAL COMPOSITION (%)											COMPOSICIÓN QUIMICA (%)					MECHANICAL TESTS (PROP. MECANICAS)				
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 15T	ELG % 2ND	RED % 3RD	BHN AVG				
BODY CUERPO	CAX	ASTM A-105N	0.220	0.720	0.022	0.008	0.270	0.050	0.030	0.020	0.050			79.31	52.92	35	54	170				
BODY CUERPO	CCH	ASTM A-105N	0.230	0.680	0.019	0.007	0.250	0.100	0.100		0.220			78.30	52.20	27	58	170				
BODY CUERPO	CCJ	ASTM A-105N	0.220	0.890	0.020	0.007	0.210	0.100	0.100	0.100				79.02	55.10	32	60	170				
YOKE YUGO	CAV	ASTM A-105N	0.230	0.810	0.018	0.007	0.240	0.050	0.050	0.100	0.220	0.010		76.12	50.75	32	54	170				



COPIA CONTROLADA


Sandra Ruiz