MILL'S QUALITY CERTIFICATE

SeAH Steel Corp.
(주)세 아 제 강

HEAD OFFICE ; BONGNAE-DONG 1GA, JUNG-GU, SEOUL, KOREA
POHANG PLANT ; 14-1, JANGHEUNG-DONG, NAM-GU, POHANG

증명서번호 CERTIFICATE NO. : E200706-0020-001526(5001625)
제 품 명 COMMODITY : E.R.W STEEL PIPE
제 품 규 격 SPECIFICATION : API 5LB PSL1/ASTM A53B(2006)

발 급 일 자 DATE OF ISSUE : 2007.04.30
계 약 서 번 호 L/C No. (P/O No.) : 47LI-B93402-TMA4
수 요 가 CUSTOMER : DUFERCO SA
주 문 자 SHIPPER : SEAH STEEL CORPORATION

NO.	HEAT NO. (BATCH NO.)	관 단 TYPE *1	주 문 치 수 ORDER SIZE	수 량 QUANTITY 본 수 PCS	총 길 이 TOTAL LENGTH	중량(M/T) WEIGHT	비 고 REMARK
23	SQ05286 (SHH4162110)	BBE	10 " X 0.250 " X 6.120 M	71	434.520 M	18.289	
24	C720288 (SHH4171010)	BBE	10 " X 0.250 " X 6.120 M	142	869.040 M	36.578	
25	C720529 (SHH4172090)	BBE	10 " X 0.500 " X 6.120 M	52	318.240 M	25.952	
26	C720529 (SHH4181010)	BBE	10 " X 0.500 " X 6.120 M	54	330.480 M	26.951	

NO.	HEAT NO (BATCH NO.)	HYDROSTATIC TEST 5 Sec. psi	RESULT	N·D·T U *2	VISUAL & DIMENSION	FLATTENING	SHOCK	COMPRESSION	RESIDUAL MAGNETISM GAUSS	BENDING *3	DRIFT	CRUSH	FLARING	FLANGE	REVERSE FLATTENING	ZINC COATING TEST WEIGHT OF ZINC COAT-ING	규일량 C.S *4	알칼리 ALK *5	DESIG *6	C	Si	Mn	P	S	CU	NI	CR	MO	V	CEQ *8	DIR *9	TENSILE STRENGTH psi	YIELD STRENGTH psi	E.L % *10	IMPACT TEST (℃) ENE-RGY Joule	SHEAR AREA %	HARD-NESS TEST	HEAT TREAT MENT SN *11	PROTECTIVE COATING & LINING THICK-NESS	P.H
																				CHEMICAL COMPOSITION(%)														TENSILE TEST (Gage Length : 50mm)			IMPACT TEST (℃)					
기준 SPEC									30										MAX	26		120	30	30	40	40	40	15	80											
																			MIN												60000	35000							
23	SQ05286 (SHH4162110)	980	G	G	G	G			G										H	15	1	66	10	2														
																			P	15	2	65	10	TR	1	1	1	TR	TR	T	69690	50060	40				G		
																			P	16	2	67	8	TR	TR	1	1	TR	TR	W	69268								
24	C720288 (SHH4171010)	980	G	G	G	G			G										H	16	1	73	15	8														
																			P	15	TR	72	15	10	1	1	1	TR	1	T	74950	57880	40				G		
																			P	15	1	73	17	7	1	1	1	1	1	W	75384								
25	C720529 (SHH4172090)	1950	G	G	G	G			G										H	14	2	79	20	4														
																			P	13	2	79	18	3	1	1	1	1	TR	T	77940	59450	45				G		
																			P	13	2	78	21	4	1	1	1	1	1	W	77659								
26	C720529 (SHH4181010)	1950	G	G	G	G			G										H	14	2	79	20	4														
																			P	14	3	79	20	4	1	1	1	1	1	T	77510	60160	44				G		
																			P	15	2	79	21	4	1	1	1	1	2	W	78513								

NOTE *1 ~ *12 : Refer To The Attached Section Designation

OTHER

Surveyor :

- WE HEREBY CERTIFY THAT THE MATERIAL HEREIN HAS BEEN MADE AND TESTED IN ACCORDANCE WITH ABOVE SPECIFICATION AND THE RESULTS OF ALL TEST ARE ACCEPTABLE.
- THE USE OF THE MATERIAL OUTSIDE THE SPECIFICATIONS INDICATED ON THIS CERTIFICATE MAY CAUSE SAFETY AND/OR MONETARY PROBLEMS. FURTHERMORE, ANY ORGANIZATION OR PERSON(S) WHO DELIBERATELY MODIFIES THE CERTIFICATE WILL BE PROSECUTED FOR FORGING AN OFFICIAL DOCUMENT (ACCORDING TO THE PROVISIONS OF THE CRIMINAL CODE 231)

Manager of Q.M Dept.

J.E. KIM

주식회사세아제강 SeAH 포항공장품질경영팀장