MILL'S QUALITY CERTIFICATES

SeAH Steel Corp.
(주)세 아 제 강

HEAD OFFICE ; BONGNAE-DONG 1GA, JUNG-GU, SEOUL, KOREA
POHANG PLANT ; 14-1, JANGHEUNG-DONG, NAM-GU, POHANG

증명서번호 / CERTIFICATE NO. : E200709-0084-002320(5001625)
제 품 명 / COMMODITY : E.R.W STEEL PIPE
제 품 규 격 / SPECIFICATION : API 5LB PSL1/ASTM A53B(2006)

발 급 일 자 / DATE OF ISSUE : 2007.08.31
계 약 서 번 호 / L/C No. (P/O No.) : PLESA
수 요 가 / CUSTOMER : DUFERCO SA
주 문 자 / SHIPPER : SEAH STEEL CORPORATION

NO.	HEAT NO. (BATCH NO.)	관 단 TYPE *1	주 문 치 수 ORDER SIZE			수 량 QUANTITY 본 수 PCS	총 길 이 TOTAL LENGTH	중량(M/T) WEIGHT	비 고 REMARK
1	SQ09808 (SIH6051090)	BBE	20 "	X 0.250 "	X 6.120 M	2	12.240 M	0.969	
2	C732961 (SIH6252140)	BBE	24 "	X 0.250 "	X 6.120 M	1	6.120 M	0.583	
3	C732959 (SIH6252170)	BBE	24 "	X 0.250 "	X 6.120 M	30	183.600 M	17.490	
4	C722814 (SIH7111050)	BBE	24 "	X 0.250 "	X 6.120 M	12	73.440 M	6.996	

NO.	HEAT NO (BATCH NO.)	HYDROSTATIC TEST 10 Sec. psi	RESULT	N·D·T U *2	VISUAL & DIMENSION	FLATTENING	SHOCK	COMPRESSION	RESIDUAL MAGNETISM GAUSS	BENDING *3	DRIFT	CRUSH	FLARING	FLANGE	REVERSE FLATTENING
기준 SPEC									30						
1	SQ09808 (SIH6051090)	530	G	G	G	G			G						
2	C732961 (SIH6252140)	440	G	G	G	G			G						
3	C732959 (SIH6252170)	440	G	G	G	G			G						
4	C722814 (SIH7111050)	440	G	G	G	G			G						

NO.	HEAT NO (BATCH NO.)	ZINC COATING TEST WEIGHT OF ZINC COAT-ING	균일성 C.S *4	알칼리 ALK *5	DESIG *6	C	Si	Mn	P	S	CU	NI	CR	MO	V	CEQ *8	DIR *9	TENSILE STRENGTH psi	YIELD STRENGTH psi	E.L % *10	IMPACT TEST (℃) ENE-RGY Joule	SHEAR AREA %	HARD-NESS TEST	HEAT TREAT MENT SN *11	PROTECTIVE COATING & LINING THICK-NESS	P.H
						*7																				
기준 SPEC					MAX	26		120	30	30	40	40	40	15	80											
					MIN													60000	35000							
1	SQ09808 (SIH6051090)				H	15	1	68	19	6																
					P	14	TR	68	20	5	1	1	1	TR	TR		T	69690	47500	36				G		
					P	14	TR	68	21	7	1	1	2	TR	TR		W	71117								
2	C732961 (SIH6252140)				H	17	2	74	13	8																
					P	16	1	74	13	10	1	1	1	1	1		T	69690	48920	39				G		
					P	16	2	74	12	7	1	1	2	1	1		W	69268								
3	C732959 (SIH6252170)				H	17	2	77	12	10																
					P	16	2	76	10	10	1	2	2	1	1		T	70970	50060	39				G		
					P	16	2	76	12	10	1	1	2	1	1		W	69694								
4	C722814 (SIH7111050)				H	18	TR	74	15	10																
					P	19	TR	75	14	9	2	2	2	1	1		T	74670	53760	38				G		
					P	17	1	75	15	12	2	2	1	TR	1		W	73535								

NOTE *1 ~ *12 : Refer To The Attached Section Designation

OTHER

Surveyor :

· WE HEREBY CERTIFY THAT THE MATERIAL HEREIN HAS BEEN MADE AND TESTED IN ACCORDANCE WITH ABOVE SPECIFICATION AND THE RESULTS OF ALL TEST ARE ACCEPTABLE.
· THE USE OF THE MATERIAL OUTSIDE THE SPECIFICATIONS INDICATED ON THIS CERTIFICATE MAY CAUSE SAFETY AND/OR MONETARY PROBLEMS. FURTHERMORE, ANY ORGANIZATION OR PERSON(S) WHO DELIBERATELY MODIFIES THE CERTIFICATE WILL BE PROSECUTED FOR FORGING AN OFFICIAL DOCUMENT (ACCORDING TO THE PROVISIONS OF THE CRIMINAL CODE 231)

Manager of Q.M Dept.

J. E. KIM

(주)세아제강 품질경영팀장