MILL'S QUALITY CERTIFICATE

SeAH Steel Corp.
(주)세 아 제 강

HEAD OFFICE ; BONGNAE-DONG 1GA, JUNG-GU, SEOUL, KOREA
POHANG PLANT ; 14-1, JANGHEUNG-DONG, NAM-GU, POHANG

증명서번호
CERTIFICATE NO.: E201004-0131-000859(5005233)

제 품 명
COMMODITY : E.R.W STEEL PIPE

제 품 규 격
SPECIFICATION : API 5LB PSL1/ASTM A53B(2007)

발 급 일 자
DATE OF ISSUE : 2010.03.31

계 약 서 번 호
L/C No. (P/O No.) : 1103077092

수 요 가
CUSTOMER : PLESA

주 문 자
SHIPPER : DUFERCO SA

NO.	HEAT NO. (BATCH NO.)	관 단 TYPE *1	주 문 치 수 ORDER SIZE	수 량 QUANTITY 본 수 PCS	총 길 이 TOTAL LENGTH	중량(M/T) WEIGHT	비 고 REMARK
9	SB66923 (SHK3251020)	BBE	14 " X 0.312 " X 6.120 M	269	1,646.280 M	111.519	CONFIRM TO NACE NORM MR0175(LAST EDITION)
10	SQ98002 (SHK3252010)	BBE	10 " X 0.250 " X 6.120 M	243	1,487.160 M	62.595	*ERW: CHEMICAL COMPOSITION, HEAT TREATMENT AND HARDNESS ONLY *DSAW:CHEMICAL COMPOSITION AND HARDNESS ONLY
11	SB64017 (SHK3302040)	BBE	10 " X 0.500 " X 6.120 M	4	24.480 M	1.997	
12	9-5487 (SHK3302050)	BBE	10 " X 0.500 " X 6.120 M	3	18.360 M	1.497	

NO.	HEAT NO (BATCH NO.)	HYDROSTATIC TEST 5 Sec. psi	RESULT	N·D·T U *2	VISUAL & DIMENSION	FLATTENING	SHOCK	COMPRESSION	RESIDUAL MAGNETISM GAUSS	BENDING *3	DRIFT	CRUSH	FLARING	FLANGE	REVERSE FLATTENING	ZINC COATING TEST WEIGHT OF ZINC COAT-ING	균일성 C.S *4	알칼리 ALK *5	DESIG *6	C	Si	Mn	P	S	Cu	Ni	Cr	Mo	V	Nb	Ti		CEQ *8	DIR *9	TENSILE STRENGTH psi	YIELD STRENGTH psi	E.L % *10	ENE-RGY Joule	SHEAR AREA %	HARD-NESS TEST	HEAT TREAT MENT SN *11
																				CHEMICAL COMPOSITION(%)															TENSILE TEST (Gage Length : 50mm)			IMPACT TEST (℃)			
																				2			3		2	2	2	2	3	3	3										
기준 SPEC									30										MAX	26		120	30	30	40	40	40	15	80												
																			MIN																	60200	35500					
9	SB66923 (SHK3251020)	950	G	G	G	G			G										H	18	1	82	15	7																	
																			P	17	TR	83	14	8	2	2	1	TR	2	2	1			T	74380	50490	34				G
																			P	18	TR	82	16	5	2	2	1	TR	2	2	1			W	76970					
10	SQ98002 (SHK3252010)	1000	G	G	G	G			G										H	14	1	67	12	6																	
																			P	13	1	68	10	5	1	1	TR	TR	2	1	TR			T	70830	50490	33				G
																			P	15	2	66	11	5	1	1	TR	TR	2	1	TR			W	72290					
11	SB64017 (SHK3302040)	1990	G	G	G	G			G										H	17	2	76	15	6																	
																			P	16	1	77	13	7	2	1	1	TR	2	1	2			T	72110	51630	37				G
																			P	17	2	76	16	4	2	1	1	TR	2	1	2			W	73840					
12	9-5487 (SHK3302050)	1990	G	G	G	G			G										H	16	18	62	17	6																	
																			P	16	18	61	19	8	1	2	TR	TR	2	1	TR			T	70970	56040	38				G
																			P	15	18	62	16	6	1	2	TR	TR	2	1	TR			W	75410					

NOTE *1 ~ *11: Refer To Others

OTHERS
*1-BBE:Black Beveled End(30°)
*2-U:Weld Seam Ultrasonic Test
*6-H:Heat(Ladle) Analysis, P:Product Analysis *7-2:X100, 3:X1000
*9-T:Base Metal Transverse, W:Weld Part Transverse *10-E.L:Elongation *11-S.N:Seam Normalizing *G:GOOD *Tr:Trace

Surveyor :

- WE HEREBY CERTIFY THAT THE MATERIAL HEREIN HAS BEEN MADE AND TESTED IN ACCORDANCE WITH ABOVE SPECIFICATION AND THE RESULTS OF ALL TEST ARE ACCEPTABLE.
- THE USE OF THE MATERIAL OUTSIDE THE SPECIFICATIONS INDICATED ON THIS CERTIFICATE MAY CAUSE SAFETY AND/OR MONETARY PROBLEMS. FURTHERMORE, ANY ORGANIZATION OR PERSON(S) WHO DELIBERATELY MODIFIES THE CERTIFICATE WILL BE PROSECUTED FOR FORGING AN OFFICIAL DOCUMENT (ACCORDING TO THE PROVISIONS OF THE CRIMINAL CODE 231)

Manager of Q.M Dept.
N. J. Baek