MILL'S QUALITY CERTIFICATE

SeAH Steel Corp.
(주)세 아 제 강

HEAD OFFICE ; BONGNAE-DONG 1GA, JUNG-GU, SEOUL, KOREA
POHANG PLANT ; 14-1, JANGHEUNG-DONG, NAM-GU, POHANG

증명서번호
CERTIFICATE NO.: E201004-0134-000862(5005298)
제 품 명
COMMODITY : E.R.W STEEL PIPE
제 품 규 격
SPECIFICATION : API 5LB PSL1/ASTM A53B(2007)

발 급 일 자
DATE OF ISSUE : 2010.03.31
계 약 서 번 호
L/C No. (P/O No.) : 1103077721
수 요 가 :
CUSTOMER : PLESA
주 문 자 :
SHIPPER : DUFERCO SA

NO.	HEAT NO. (BATCH NO.)	관 단 TYPE *1	주 문 치 수 ORDER SIZE	수 량 QUANTITY 본 수 PCS	총 길 이 TOTAL LENGTH	중량(M/T) WEIGHT	비 고 REMARK
5	SA39163 (SHK3152030)	BBE	12 " X 0.250 " X 6.120 M	92	563.040 M	28.214	CONFIRM TO NACE NORM MR0175(LAST EDITION)
6	SB67815 (SHK3231060)	BBE	14 " X 0.250 " X 6.120 M	144	881.280 M	48.567	*ERW: CHEMICAL COMPOSITION, HEAT TREATMENT AND HARDNESS ONLY
7	SB66163 (SHK3232010)	BBE	14 " X 0.375 " X 6.120 M	3	18.360 M	1.489	*DSAW:CHEMICAL COMPOSITION AND HARDNESS ONLY
8	SB66168 (SHK3232030)	BBE	14 " X 0.375 " X 6.120 M	3	18.360 M	1.489	

NO.	HEAT NO (BATCH NO.)	HYDROSTATIC TEST 5 Sec. psi	RESULT	N·D·T U *2	VISUAL & DIMENSION	FLATTENING	SHOCK	COMPRESSION	RESIDUAL MAGNETISM GAUSS	BENDING *3	DRIFT	CRUSH	FLARING	FLANGE	REVERSE	FLATTENING	ZINC COATING TEST WEIGHT OF ZINC COAT-ING	균일성 C.S *4	알칼리 ALK *5
기준 SPEC									30										
5	SA39163 (SHK3152030)	840	G	G	G	G			G										
6	SB67815 (SHK3231060)	770	G	G	G	G			G										
7	SB66163 (SHK3232010)	1150	G	G	G	G			G										
8	SB66168 (SHK3232030)	1150	G	G	G	G			G										

NO.	HEAT NO (BATCH NO.)	DESIG *6	C	Si	Mn	P	S	Cu	Ni	Cr	Mo	V	Nb	Ti		CEQ *8	DIR *9	TENSILE STRENGTH psi	YIELD STRENGTH psi	E.L % *10	ENERGY Joule	SHEAR AREA %	HARDNESS TEST HRC	HEAT TREATMENT SN *11
			2			3		2	2	2	2	3	3	3										
			*7																					
기준 SPEC		MAX	26		120	30	30	40	40	40	15	80											22	
		MIN																60200	35500					
5	SA39163 (SHK3152030)	H	15	2	69	15	7																	
		P	14	2	68	16	9	TR	TR	1	TR	TR	1	1			T	70920	51340	36			7	G
		P	16	2	69	14	5	TR	TR	1	TR	TR	1	1			W	77300						
6	SB67815 (SHK3231060)	H	15	1	63	12	9																	
		P	14	1	62	13	7	1	TR	1	TR	2	2	2			T	67730	57870	27			7	G
		P	15	1	64	12	7	1	TR	1	TR	2	2	2			W	76430						
7	SB66163 (SHK3232010)	H	17	1	73	15	5																	
		P	18	1	72	15	7	1	TR	TR	TR	TR	1	TR			T	70920	49310	36			8	G
		P	18	2	73	14	5	1	TR	TR	TR	TR	1	TR			W	78610						
8	SB66168 (SHK3232030)	H	20	2	76	15	6																	
		P	20	1	77	17	4	TR	1	2	TR	2	2	1			T	76870	53220	34			7	G
		P	21	1	77	14	4	TR	1	2	TR	2	2	1			W	80780						

NOTE *1 ~ *11: Refer To Others

OTHERS
*1-BBE:Black Beveled End(30°)
*2-U:Weld Seam Ultrasonic Test
*6-H:Heat(Ladle) Analysis, P:Product Analysis *7-2:X100, 3:X1000
*9-T:Base Metal Transverse, W:Weld Part Transverse *10-E.L:Elongation *11-S.N:Seam Normalizing *G:GOOD *Tr:Trace

Surveyor :

· WE HEREBY CERTIFY THAT THE MATERIAL HEREIN HAS BEEN MADE AND TESTED IN ACCORDANCE WITH ABOVE SPECIFICATION AND THE RESULTS OF ALL TEST ARE ACCEPTABLE.
· THE USE OF THE MATERIAL OUTSIDE THE SPECIFICATIONS INDICATED ON THIS CERTIFICATE MAY CAUSE SAFETY AND/OR MONETARY PROBLEMS. FURTHERMORE, ANY ORGANIZATION OR PERSON(S) WHO DELIBERATELY MODIFIES THE CERTIFICATE WILL BE PROSECUTED FOR FORGING AN OFFICIAL DOCUMENT (ACCORDING TO THE PROVISIONS OF THE CRIMINAL CODE 231)

Manager of Q.M Dept.
N. J. Baek