



FLM-005-7  PROCARSA, S.A. DE C.V.	CERTIFICADO DE CALIDAD DE PRUEBAS FISICAS-QUIMICAS QUALITY CERTIFICATE OF TEST PHYSICALS-CHEMICAL	CLIENTE: PLESA ANAHUAC Y CIAS. S.A. DE C.V. CUSTOMER:	NUMERO PTM-6546-2017 NUMBER
		PEDIDO CLIENTE / P.O. N/A PEDIDO INTERNO / I.O.	FECHA SEPTIEMBRE 14, 2017 DATE
		PARTIDA (S) N/A ITEMS	
		PRESION HIDROSTATICA: N/A HIDROSTATIC TEST:	

TAMAÑO N/A SIZE:	ESPESOR DE PARED N/A WALL THICKNESS	GRADO: N/A GRADE:	PRESION HIDROSTATICA: N/A HIDROSTATIC TEST:
---------------------	--	----------------------	--

PRUEBAS DE TENSION TENSILE TEST							ANALISIS QUIMICO % EN PESO CHEMICAL ANALYSES PERCENT WEIGHT															
PARTIDA ITEM	NUM.PROBETA DESCRIPTION	COLADA HEAT	LIMITE ELASTICO YIELD STRENGTH (P.S.I.)	ULTIMA TENSION TENSILE STRENGTH (P.S.I.)	% ELONG. 2"	LE/UT Y.S/T.S	C	Mn	P	S	Cb	V	Ti	Si	Cu	Al	Ca	Cr	Ni	Mo	N	Ceq
1	1-10 Lc	217573	52 282	61 790	42	0.84	0.103	0.77	0.017	0.004	--	--	--	0.211	0.021	0.028	0.0045	0.013	0.015	--	--	
2	7-17 Lc	422698	54 201	65 387	39	0.82	0.117	0.77	0.013	0.008	--	--	--	0.206	0.025	0.038	0.0026	0.020	0.023	--	--	
3	3-3 Lc	223253	50 790	65 839	37	0.77	0.122	0.78	0.013	0.004	--	--	--	0.218	0.015	0.023	0.0034	0.025	0.014	--	--	

PARTIDA ITEMS	DIMENSIONES SIZE	GRADO GRADE	PARTIDA ITEM	No. PEDIDO P.O.
1	8" X 8" X 0.250"	ASTM A500-B	123316-20	16430
2	8" X 8" X 0.375"	ASTM A500-B	129598-20	16430
3	10" X 10" X 0.312"	ASTM A500-B	129598-60	16430

CERTIFICAMOS QUE LA TUBERIA AQUÍ DESCRITA CUMPLE Y HA SIDO FABRICADA, MUESTREADA, PROBADA E INSPECCIONADA DE ACUERDO CON LOS REQUISITOS APLICABLES DE LA ESPECIFICACION: ASTM A500 -- --	WE CERTIFY THE PIPE ABOVE MENTIONED ACCOMPLISH AND HAS BEEN MANUFACTURED, SAMPLED, TESTED AND INSPECTED IN ACCORDANCE WITH APPLICABLE REQUIREMENTS OF SPECIFICATIONS: -- -- --	 ING. LUIS ALFONSO DE LOS SANTOS RIVERA SUPERVISOR DE LABORATORIO METALURGICO METALLURGICAL LABORATORY SUPERVISOR
--	---	--