Material Test Report

Heat Code: AWX

An Ameri-Forge Group Company 13770 Industrial Rd., Houston, TX 77015

ISO 9001:2000 Certified

Sales: (713) 868-4421 Fax: (713) 455-8366

PLESA ANAHUAC Y CIAS SA DE CV AV. VALLE DE LAS

ALAMEDAS 66-0

54940 TULTITLAN, EDO MEX

PO: 5101

Supplier: CMC

Sales Order: 66536

Line: 22

Item Code: 0155200102-0020F Qty Shipped: 2

Item Desc: FLG 02.00 0150 SW RF XH A105

NHT COFFR Supplier Heat: 3002422

Spec: ASME SA-105/SA-105M 2004 Section II/ASTM A105/A105M-03

C	Elem	ent (%wt)	Ladle	Product	EPCR/	CAS#	Element	(%wt)	Ladie	Product	EPCRA	CAS#
P Phosphorous 0.007 V Vanadium 0.001 S sulphur 0.018 C.E. 0.417 Si silicon 0.21 CuNiCrMo 0.46 Cu Copper 0.24 ✓ 7440-50-8 CrMo 0.11	С	Carbon	0.22				Cr Chromi	TIM	0.07		✓ 7	440-47-3
P Phosphorous 0.007 V Vanadium 0.001 S Sulphur 0.018 C.E. 0.417 Si Silicon 0.21 CuNiCrMo 0.46 Cu Copper 0.24 ✓ 7440-50-8 CrMo 0.11	Mn	Manganese	0.91		✓	7439-96-5	Mo Molybo	lenum	0.038			
Si Silicon 0.21 CuNiCrMo 0.46 Cu Copper 0.24 ✓ 7440-50-8 CrMo 0.11	Р	-	0.007				V Vanadi	um	0.001			
Cu Copper 0.24		•	0.018				C.E.		0.417			
Cu copper 0.24 √ 7440-50-8 CrMo 0.11	Si	Silicon	0.21				CuNiCrMo		0.46			
(7440 00 0 :			0.24		✓	7440-50-8	CrMo		0.11			
		Nickel	0.11		✓	7440-02-0						

Mechanical		Other	
Test Lab	AFG	Country of Origin	USA (US)
Test Bar Size	SACRIFICIAL PIECE	EF	Y
HBW	159-159		
Elg (%)	25.0		
RA (%)	65.0		
Tensile Specimen Size (in)	0.246		
Tensile (ksi)	79.0		
Yield (ksi)	48.7		
Gauge Length	1.00		
		1, 1	
,			
•			

Product compliant with NACE MR0175 / ISO 15156, latest edition and dimensions to ANSI B16.5 Product compliant with and meets all requirements of ASTM Al05/ASME SA105, latest edition.

Chemical Analysis results shown are actual. Forgings are capable of passing No Weld repair performed. hydrostatic test compatible with the appropriate rating. Elongation taken from a round specimen. All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing. Yield strength was determined using the 0.2% offset method.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.:

152580

Certification Date:

10/23/2008

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b

Vielales Legere

Nicholas Tepovich - Metallurgic Lab Manager