

www.smt.sandvik.com www.smt.sandvik.com/nafta

Sandvik Materials Technology

Product Area Tube P.O. Box 1220 Scranton PA USA 18501 570-585-7500

2009048

Page 1

Ship To: Sold To: 632580

GAISA FORWARDING INC SANDVIK DE MEXICO

LAREDO TX TLALNEPANTLA, EDO MEXICO

Customer Order No: 6P0846 Sandvik Order No: 71506/3

Work Order/Lot: 524517

ASTM A312-07, ASME SA-312, ASTM A376-06, ASME SA-376, ASME Section 2007 Edition, NACE MR0175 / ISO 15156, First edition 2003-12-15 (Austenitic)

Hot Finished PROCESS ANNEALED AND PICKLED Seamless Pipe

Size: 1" SCH 40 Type TP304/TP304L (UNS S30400/S30403)

Heat: 520906

Certification Date: 200902

Material Manufacturer: Pennsylvania Extruded Tube Co. USA

ANALYSIS % Si Mn C .025 .007 .35 1.20 18.38 .004 Heat .006 18.35 1.19 .026 .006 .36 Prod Pb Αl Fe Mo

.37 .005 Heat .003 .37 Prod

Mechanical Tests:

Elongation Tensile Yield Strength Strength in % 1.0% psi MPa MPa E2" E10" E4d E5d psi MPa psi 594.5 59 N/A N/AN/A34000 234.5 N/A86200

Hardness Test Results: 79HRB, 80HRB Hydrostatic Test (psi): 2500

Flattening Test per ASTM A999: Acceptable Tensile Test sample width (1=Full-Size 2=1/2" Strip): 1 Corrosion Test per ASTM A262 Pr.E, MIL-P-24691/3 and MIL-P-1144D. No. samples: 1 Result: Acceptable

Country Of Origin: United States

This Material complies with FAR BAA (FAR 52.225-1)

This Material complies with DFARS BAA (DFARS 252.225-7001)

and FAR TAA(FAR $5\overline{2}.225-5$)

All material subjected to a final solution annealing heat treatment with material at a temperature of 1900 deg. F minimum followed by rapid quenching to below 800 deg. F in less than three (3) minutes.

The material has not come in contact with Mercury or Mercury

containing compounds.
No welding has been performed on this material.

Material has been manufactured/supplied in accordance with Sandvik Materials Technology Quality Manual-Standard Products Revision 10 dated May 29, 2007. Quality system has been approved to ISO 9001:2000.

Certificate produced in accordance with EN 10204 3.1

(formerly EN 10204 3.1.B)

Melt Source: AB Sandvik MT, Sweden

Melt Method: Electric Arc Furnace-AOD Refining