

SOUTHERN CALIFORNIA VALVE 13903 MARYTON AVENUE SANTA FE SPRINGS, CA 90670

MATERIAL TEST CERTIFICATE

PHONE: (800)	554-6421	(281) 482-4728	FAX: (562	2) 356-2849
--------------	----------	----------------	-----------	-------------

DATE: 8/10/11

CUSTOMER

SCV ORDER #: 23840

ITEM #: 1

PETROMAX INTERNATIONAL P.O.# 08.09.PLS.11 QUANTITY: 1

SCV FIG # BAL0401B1036RLFF

SERIAL NUMBER

99555

DESCRIPTION 4" 150 FLOATING BALL VALVE WCB BODY 316SS TRIM RF FP LEVER OPERATED

150

PASSED HYDROTEST RESULTS PRESSURE: PSI TESTED TO: API 6D SHELL SEAT SEAT В BACKSEAT CLASS Hydro Hvdro Air Hydro Air Hydro 325 325 450

HEAT TREATMENT 1650°F~ Normalize

COMPLIES WITH NACE MR-0175 FIRESAFE TO API 607

SIZE 4

HOLDING TIME: MINUTES

			MATERIAL: ASTM A216, WCB										PHYSICALS						
				CHEMICALS								TENSILE		YIELD %	%	%	BHN		
Part	Heat #	C.	Mn.	P.	S.	Si.	Cu.	Ni.	Cr.	Mo.	V.		MPA	MPA	EL	RA			
		.30mx	1.00mx	.04mx	.045mx	.60mx	.30mx	.50mx	.50mx	.20mx	.03mx		485-655	250min	22min	35min	137-187		
BODY & ENDS	E1E13	0.17	0.68	0.020	0.020	0.43	0.13	0.14	0.14	0.16	0.010		524	290	35	43	1		
·													<u> </u>						
						• • • • • • • • • • • • • • • • • • • •													
													 	<u> </u>					
	1	I	1		1 30 4		1				l	I	I .	l		1	, ,		

Our letters are for the exclusive use of the client to whom they are addressed. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected. And are not necessarily indicative of the qualities of apparently identical or similar products. We certify the materials meet the referenced specifications as reported on the material manufacturer's test certificates which are maintained in our files. The information contained in this report is true and correct to the best of my knowledge. This report is issued by the Quality Assurance Department which is independent of the Manufacturing or Processing Department. It conforms to DIN Standard 10204-31B and to ISO Standard 10474-3.1B.

QUALITY ASSURANCE