

CERTIFICATE OF INSPECTION & TEST

ORIGINAL




ST&H CORPORATION
 411-3 Shinwol-ri, Jinryemyun, Gimhae-si Gyungnam, Korea
 Tel: 82.51.744-4680(5 line) Fax: 82.51.744-4670
 E-mail: stcorp@kornet.net

(EN 10204 3.1)

Certified to ISO9001:2008, ISO14001:2004, PED97/23/EC by LRQA

Certified API Spec Q1 and API Spec 6A (Licence No : 6A-1284)



Customer : PLESA ANAHUAC Y CIAS..S.A DE C.V.				Contract No. : 15982				Report No : MSH8188				Date: SEP.09.2013			
Spec. For Material : ASTM/ASME A/SA105N-11(NACE MR0175/ISO 15156-2009)												Heat Treatment			
Chemical Composition (%)		C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	910°C NORMALIZED & A.C			
Heat No./Batch no.	MAX	0.350	0.350	1.050	0.035	0.040	0.400	0.300	0.120	0.400	0.080				
	MIN		0.100	0.600											
T1066L		0.213	0.233	0.940	0.018	0.011	0.026	0.066	0.002	0.023	0.002	Dimensional Inspection			
Tension Test						Charpy Impact Test (10x10 mm Specimen Size)				Hardness Test (HB)	Bending Test 90:120(180°)				
Size of Specimen(mm)		Yield Strength MPa	Tensile Strength MPa	Elongation %	Red of Area %	Individual		Average				Notch Type			
Dia	Gage Length					min	min	Temp							
12.5	50	MAX				Test Result				187					
		MIN	250.000	485.000	22.000	30.000	①	②	③	Average					
12.5	50		297.000	521.000	38.000	60.000					146, 147				
ITEM / SIZE		Q'TY		ITEM / SIZE		Q'TY		ITEM / SIZE		Q'TY		Ultrasonic Examination N/A Magnetic Particle Examination N/A Remarks : **CE = 0.39 (LONG FORMULAR)			
150LBS SORF 3"		500		BLANK				BLANK							
BLANK															

NOTE :
 1MPa = 145.037 psi
 1MPa = 0.145037 ksi
 1psi = 0.006895 MPa
 1ksi = 6.89476 MPa

W.C:Water Cool O.C:Oil Cool
 A.C:Air Cool N.A:Non Action
 N:Normalized A:Annealed
 Q.T:Quenched and Tempered
 N.T:Normalized and Tempered

We hereby certify that the material herein has been made and tested in accordance with the above specification and also with the requirements called for by the above order.

[Signature]



Witnessed by / H. J. LEE Manager of Q.A Dept. / S. H. LEE