

CERTIFICADO DE CALIDAD INSPECTION CERTIFICATE (DIN EN 10204:2004E - ISO 10474 3.1.B)		Número: Number:	Página/Page:
		23120	1 DE 1

Vendido a: Sold to:	PLESA ANAHUAC Y CIA. S.A. DE C.V.	Pedido del Cliente No: Customers Order No:	7558 -	Lista de Empaque: Packing List:	11800	Fecha/Date:	13 de Enero de 2010
Especificaciones y Grados / Standard or Specification and Steel Grade Seamless Fittings according to ASTM A 234M WPB-07, NACE MR 01.75-2003 Conform to ASME II Ed. 2001 ASME SA-234M Grade WPB, NACE MR0103-2003		Dimensiones y tolerancias / Dimension and tolerances ASME B 16.9 - 2007 and ASME B 16.28 - 1994			Factura/Invoice: Bocas / Ends Biselado / Bevelled ends		


DESCRIPCION DE MATERIAL / MATERIAL DESCRIPTION				PRUEBAS MECANICAS / MECHANICAL TEST				PRUEBA DE IMPACTO 0°C / IMPACT TEST 0°C				
ART. ITEM	COLADA HEAT CODE	CANTIDAD QUANTITY	DESCRIPCION / DESCRIPTION	ESF. CEDENCIA YIELD STRENGTH (Mpa)	ESF. RUPTURA TENSILE STRENGTH (Mpa)	ELONG. %2"	DUREZA HARDNESS HBW	DIMENSIONES SAMPLE DIM mm	1 Joules	2 Joules	3 Joules	PROMEDIO AVERAGE Joules
1	T46926	100	CODO 6 X 90° R.L. CED-STD.	355	496	39	117					

ANALISIS QUIMICO / CHEMICAL ANALYSIS														
PROCESO PROCESS	COLADA HEAT CODE	COLADA/HEAT M.P./MOTHER PIPE	%C.E.	%C	%Mn	%P	%S	%Si	%Cr	%Cu	%Mo	%Ni	%V	%Nb
HF	T46926	46926	0.310	0.170	0.690	0.010	0.003	0.290	0.040	0.063	0.038	0.030	0.000	0.000

Certificamos que los resultados de los Análisis Químicos y Pruebas Mecánicas son verdaderos o una copia fiel de los certificados enviados por el Fabricante y/o el proveedor de Materia Prima (Tubería Sin Costura) conforme ASTM A106 Grado B con N°: 9065506

We certify that result of chemical analysis and mechanical test are true and correct copy of the test certificate issued by the manufacturer and/or supplier Raw material (Seamless Pipe) certs conform to ASTM A106 Grade B N°: 9065506

Este material cumple con los requerimientos especificados en la orden".
The material of this certificate heat number mentioned above is in compliance with the requirements specified in the order".

<p>Notas:</p> <p>Formado en caliente a 620°C-980°C, enfriado al aire; Formado en frío normalizado a 940°C max.</p> <p>Tiempo de permanencia 10'.</p> <p>Inspección Dimensional: Satisfactoria.</p> <p>HF: FORMADO EN CALIENTE/HOT FORMED</p>	<p>Notes:</p> <p>Hot formed fittings in a range from 620°C to 980°C, cooled in still air, Cold formed normalized at 940°C max.</p> <p>Holding time 10'.</p> <p>Visual dimensional check: Satisfactory</p> <p>CF: FORMADO EN FRIO/COLD FORMED</p>	 Quality Manager/Jefe de Calidad: ING. WALDO GALLEGOS GALVAN	<p>The Products described herein were produced in accordance with the above referenced specification and are identified with the "R" which is permanently marked on each fitting./ The values of hardness for fittings NPS 2 1/2" and smaller ones obtain from the conversion of hardness Rockwell B to hardness Brinell HBW by means of table WILSON DESK CHART 60.</p> <p>Los valores de dureza para conexiones de NPS de 2 1/2" y menores, se obtienen de la conversión de dureza Rockwell B a dureza Brinell HBW mediante la tabla WILSON DESK CHART 60.</p>
--	--	---	--