

**CERTIFICADO DE CALIDAD
INSPECTION CERTIFICATE**
(DIN EN 10204:2004E - ISO 10474 3.1.B)

Número:
Number:

23706

Página/Page:

1 DE 1

Tubbs de Acero de México, S.A.
Carr. Mty-Laredo Km 24.2
Apartado Postal 43
(65550) C. de Flores, N.L. Méx.
(52) 81 8305 9600 tel
(52) 81 8305 9620 fax

Vendido a: Sold to:	PLESA ANAHUAC Y CIA. S.A. DE C.V.	Pedido del Cliente No: Customers Order No:	8701 -	Lista de Empaque: Packing List:	12133	Fecha/Date:	13 de Agosto de 2010
Especificaciones y Grados / Standard or Specification and Steel Grade	Seamless Fittings according to ASTM A 234M WPB-07, NACE MR 01.75-2003 Conform to ASME II Ed. 2001 ASME SA-234M Grade WPB, NACE MR0103-2003	Dimensiones y tolerancias / Dimension and tolerances	ASME B 16.9 - 2007 and ASME B 16.28 - 1994		Factura/Invoice: Bocas / Ends Biselado / Bevelled ends		


DESCRIPCION DE MATERIAL / MATERIAL DESCRIPTION				PRUEBAS MECANICAS / MECHANICAL TEST				PRUEBA DE IMPACTO 0°C / IMPACT TEST 0°C				
ART. ITEM	COLADA HEAT CODE	CANTIDAD QUANTITY	DESCRIPCION / DESCRIPTION	ESF. CEDENCIA YIELD STRENGTH (Mpa)	ESF. RUPTURA TENSILE STRENGTH (Mpa)	ELONG. %2"	DUREZA HARDNESS HBW	DIMENSIONES SAMPLE DIM mm	1 Joules	2 Joules	3 Joules	PROMEDIO AVERAGE Joules
1	SGZ5	10	CODO 3 1/2 X 90° R.L. CED-XS	346	500	44	143					
2	OL5	10	CODO 3 1/2 X 90° R.L. CED-XS	319	480	41	98					
3	T38167	2	TEE RED. 12 X 10 CED-STD	244	466	39	96					
4	T38642	3	TEE RED. 12 X 10 CED-STD	269	463	40	107					
5	R71005	50	CODO 1 X 45° CED-STD	329	462	46	110					

ANALISIS QUIMICO / CHEMICAL ANALYSIS														
PROCESO PROCESS	COLADA HEAT CODE	COLADA/HEAT M.P./MOTHER PIPE	%C.E.	%C	%Mn	%P	%S	%Si	%Cr	%Cu	%Mo	%Ni	%V	%Nb
HF	SGZ5	22039	0.334	0.190	0.760	0.012	0.001	0.310	0.030	0.050	0.020	0.050	0.001	0.001
HF	OL5	21484	0.324	0.190	0.720	0.012	0.001	0.300	0.030	0.060	0.010	0.020	0.001	0.001
HF	T38167	38167	0.290	0.160	0.680	0.008	0.001	0.280	0.060	0.050	0.018	0.030	0.000	0.000
HF	T38642	38642	0.310	0.170	0.670	0.012	0.002	0.270	0.040	0.050	0.040	0.090	0.000	0.000
HF	R71005	71005	0.310	0.170	0.720	0.009	0.002	0.210	0.050	0.018	0.018	0.080	0.001	0.001

Certificamos que los resultados de los Análisis Químicos y Pruebas Mecánicas son verdaderos o una copia fiel de los certificados enviados por el Fabricante y/o el proveedor de Materia Prima (Tubería Sin Costura) conforme ASTM A106 Grado B con N°: 151500 150428 9002214 8023126 2270324

We certify that result of chemical analysis and mechanical test are true and correct copy of the test certificate issued by the manufacturer and/or supplier Raw material (Seamless Pipe) certs conform to ASTM A106 Grade B N°: 151500 150428 9002214 8023126 2270324

"Este material cumple con los requerimientos especificados en la orden".
The material of this certificate heat number mentioned above is in compliance with the requirements specified in the order".

Notas: Formado en caliente a 620°C-980°C, enfriado al aire; Formado en frío normalizado a 940°C max. Tiempo de permanencia 10'. Inspección Dimensional: Satisfactoria. HF: FORMADO EN CALIENTE/HOT FORMED	Notes: Hot formed fittings in a range from 620°C to 980°C, cooled in still air. Cold formed normalized at 940°C max. Holding time 10'. Visual dimensional check: Satisfactory CF: FORMADO EN FRIO/COLD FORMED	 Quality Manager/Jefe de Caldad ING. WALDO GALLEGOS GALVAN	The Products described herein were produced in accordance with the above referenced specification and are identified with the "R" which is permanently marked on each fitting. The values of hardness for fittings NPS 2 1/2" and smaller ones obtain from the conversion of hardness Rockwell B to hardness Brinell HBW by means of table WILSON DESK CHART 60. Los valores de dureza para conexiones de NPS de 2 1/2" y menores, se obtienen de la conversión de dureza Rockwell B a dureza Brinell HBW mediante la tabla WILSON DESK CHART 60.
---	--	--	---