

MILL TEST CERTIFICATE	Number / Número 16009280	Page / Página: 1 / 4
Date / Día: Mar 16, 2016		

Customer / Cliente: PLESA ANAHUAC Y CIAS. S.A. DE C.V.		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 242297/01
Manufacture Process / Proceso de fabricación: SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto: LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie: VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones: API 5L ED45		Steel Grade / Grado de acero: B/X42-L245/L290 PSL1	Ends / Extremos: PLAIN END LISO CORTE RECTO	
Dimensions / Dimensiones: 1.32 X 0.133 INCH 33.40 X 3.40 MM	Schedule / Cédula 040	Length / Longitud: 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad: 253 Pcs/pz	Nominal Weight / Peso Nominal 1.68 LB/FT 2.52 KG/M

TENSILE TEST / ENSAYOS DE TENSION

Heat N° Colada N°	Sample N° Muestra N°	Specimen condition Condición de la probeta				Specimen dimensions Dimensiones de la probeta		Test temp Temp. de ensayo	Y.S.	U.T.S.	Y.S.	Elongation Alargamiento
		Ls	Type Tipo	Ori	Size Tamaño	Area Sección	Unit / Unidad		Unit / Unidad	U.T.S.		
							KG/MM2		KG/MM2	Req. Max.		
753031	A0674/L	B	Ss	L	3.42 X 33.37	321.80	RT	37.3	53.1	0.68	% in 2 inches Min.: Obt. %	
								TMin:	TMin:		46.00	
								TMax:	TMax:			
								LMin:	LMin:			
								LMax:	LMax:			

L: Location of the sample / Localización de la muestra Longitudinal / Longitudinal Req. Max: Maximum Required / Máximo Requerido LMax: Longitudinal Maximum / Máximo Longitudinal	B: Body / Cuerpo RT: Room Temperature / Temperatura Ambiente Obt: Obtained / Obtenido TMin: Transverse Minimum / Mínimo Transversal	Ss: Strip specimen / Rectangular EUL: Extension Under Load Method Y.S.: Yield Strength / Fluencia TMax: Transverse Maximum / Máximo Transversal	Ori: Orientation / Orientación UTS: Ultimate Tensile Strength / Resistencia LMin: Longitudinal Minimum / Mínimo Longitudinal Min: Minimum / Mínimo
---	--	--	---

TECHNOLOGICAL TEST / ENSAYOS TECNOLÓGICOS

Heat N° Colada N°	Sample N° Muestra N°	Bend Test Ensayo de Curvado
753031	A0674/L	GOOD/BUENO

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

MILL TEST CERTIFICATE

Number / Número: **16009280**
 Page / Página: **2 / 4**
 Date / Día: **Mar 16, 2016**

Customer / Cliente: PLESA ANAHUAC Y CIAS. S.A. DE C.V.		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 242297/01
Manufacture Process / Proceso de fabricación: SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto: LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie: VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones: API 5L ED45		Steel Grade / Grado de acero: B/X42-L245/L290 PSL1	Ends / Extremos: PLAIN END LISO CORTE RECTO	
Dimensions / Dimensiones: 1.32 X 0.133 INCH 33.40 X 3.40 MM	Schedule / Cédula: 040	Length / Longitud: 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad: 253 Pcs/pz	Nominal Weight / Peso Nominal: 1.68 LB/FT 2.52 KG/M

CHEMICAL COMPOSITION / COMPOSICIÓN QUÍMICA

Composition % / Composición %

		C	Mn	Si	Cr	Mo	S	P	Ni	V	Cu	Nb	Ti	
		X 100						X 1000						
Heat	H	Max												
Colada		Min												
Sample N°	P	Max												
Muestra N°		Min												
753031	H	18	95	25	11	4	1	9	130	1	160	1	2	
A0674/L	P	19	95	31	11	5	3	10	140	3	150	2	3	
A0675/L	P	19	95	31	12	5	3	10	140	3	150	2	3	

H: Heat / Colada

P: Product / Producto

Max: Maximum / Máximo

Min: Minimum / Mínimo

SUPPLEMENTARY INFORMATION / INFORMACIÓN SUPLEMENTARIA

MANUFACTURED BY TENARIS SILCOTUB
 Standard: API 5L Year: 2012 Revision: Ed2 Revision year: 45th
 Standard: ASTM A53-12 Year: 2012
 Standard: ASTM A106 Year: 2014
 NONDESTRUCTIVE TEST-EDDY CURRENT ACC. TO ASTM E309,
 HOLE DIAMETER 1.1 mm max.: WITHOUT OBJECTIONS
 NONDESTRUCTIVE TEST-EMI ACC. TO ASTM E570: WITHOUT OBJECTIONS
 AFTER EMI INSPECTION, UNTESTED ENDS HAVE BEEN CUT OFF
 MATERIAL ACC. TO ASME II PART.D TAB Y1+NACE MR 01-75+PED97/23/EC
 ACC. TO THE NORM API 5L PSL1 45TH ED.; ASTM ASME A/SA 106, A/SA 53
 WE DECLARE THAT THE MINIMUM IMPACT TEST VALUE OF 27 J AT 0°C (for carbon steel)

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

MILL TEST CERTIFICATE

Number / Número Page / Página:

16009280

3 / 4

Date / Día: **Mar 16, 2016**

Customer / Cliente: PLESA ANAHUAC Y CIAS. S.A. DE C.V.		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 242297/01
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie. VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones. API 5L ED45		Steel Grade / Grado de acero. B/X42-L245/L290 PSL1		Ends / Extremos. PLAIN END LISO CORTE RECTO
Dimensions / Dimensiones. 1.32 X 0.133 INCH 33.40 X 3.40 MM	Schedule / Cédula 040	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad. 253 Pcs/pz	Nominal Weight / Peso Nominal 1.68 LB/FT 2.52 KG/M

SUPPLEMENTARY INFORMATION / INFORMACIÓN SUPLEMENTARIA

IS GUARANTEED, WITHOUT PERFORMING THE TEST
 VISUAL AND DIMENSIONAL CONTROL HAS BEEN CARRIED OUT WITH SATISFACTORY RESULT
 STEEL IS FULLY KILLED AND PRODUCED BY ELECTRIC FURNACE TO A FINE GRAIN PRACTICE
 THE PRODUCT SUPPLIED IS IN COMPLIANCE WITH THE REQUIREMENTS OF THE ORDER
 HYDROSTATIC TEST: 20.5 mpa (5 seconds): SATISFACTORY
 SUPERFICIAL HARDNESS (Max: 235.0):
 HEAT SAMPLE SC LS SCALE VAL1 VAL2 VAL3
 753031 A0674/L AM B HBW 152.0 154.0 154.0
 SC: SPECIMEN CONDITION
 AM: AS MANUFACTURED
 LS: LOCATION OF SAMPLE
 B: BODY
 VAL: VALUE
 TAMSA REF: 741918



This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

DICA 777 04 0

MILL TEST CERTIFICATE

Number / Número: **16009280**
 Page / Página: **4 / 4**
 Date / Día: **Mar 16, 2016**

Customer / Cliente: PLESA ANAHUAC Y CIAS. S.A. DE C.V.		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 242297/01
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie. VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones. API 5L ED45		Steel Grade / Grado de acero. B/X42-L245/L290 PSL1	Quantity / Cantidad. 253 Pcs/pz	Ends / Extremos. PLAIN END LISO CORTE RECTO
Dimensions / Dimensiones. 1.32 X 0.133 INCH 33.40 X 3.40 MM	Schedule / Cédula 040	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS	Nominal Weight / Peso Nominal 1.68 LB/FT 2.52 KG/M	
This is to certify that the product described here has been manufactured, sampled, tested, and inspected in accordance with purchaser order requirements. This certificate is not a declaration of origin nor may it be used as a declaration of origin.			Por el presente certificamos que el material aqui descrito ha sido fabricado, muestreado, ensayado e inspeccionado de acuerdo a los requisitos de su orden de compra. Este certificado no es, ni puede ser usado, como una declaración de origen.	
			TENARIS QUALITY DEPARTMENT SIGNATURE	
			 QUALITY CERTIFICATION DEPT. DEPTO. DE CERTIFICACIÓN DE CALIDAD NESTOR T. RODRIGUEZ C.	 CHIEF OF QUALITY CERTIFICATION DEPT. RESPONSABLE DEL DEPTO. DE CERTIFICACIÓN DE CALIDAD ANGEL CESAR ALEMÁN GIL.
This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.			Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.	