

MILL TEST CERTIFICATE		Number / Número 15023300	Page / Página: 1 / 4
		Date / Día: Jun 11, 2015	

Customer / Cliente: STOCK DISTRIBUIDORES		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 231918/01
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie. VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones. API 5L ED45		Steel Grade / Grado de acero. B/X42-L245/L290 PSL1	Ends / Extremos. PLAIN END LISO CORTE RECTO	
Dimensions / Dimensiones. 1.90 X 0.200 INCH 48.30 X 5.10 MM	Schedule / Cédula 080	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad. 91 Pcs/pz	Nominal Weight / Peso Nominal 3.63 LB/FT 5.40 KG/M

TENSILE TEST / ENSAYOS DE TENSIÓN

Heat N° Colada N°	Sample N° Muestra N°	Specimen condition Condición de la probeta				Specimen dimensions Dimensiones de la probeta		Test temp Temp. de ensayo °C	Y.S.	U.T.S.	Y.S. / U.T.S.	Elongation Alargamiento
		Ls	Type Tipo	Ori	Size Tamaño	Area Sección	Unit / Unidad		Unit / Unidad			
							KG/MM2		KG/MM2			
					mm	mm2		Required/Requerido	Required/Requerido	Req. Max.	% in 2 inches	
								TMin:	TMax:		Min.:	
								LMin:	LMax:		Obt.	
								LMax:	LMax:		%	
742609	A4084/L	B	Ss	L	13.04 X 5.18	68.60	RT	30.7	51.0	0.60	32.50	
742609	C8634/L	B	Ss	L	13.03 X 5.22	69.10	RT	32.7	50.2	0.65	31.50	
742965	A4094/L	B	Ss	L	13.00 X 5.18	68.40	RT	32.1	42.3	0.76	32.50	
742965	A8031/L	B	Ss	L	12.44 X 5.08	64.10	RT	30.7	53.8	0.57	28.50	

Ls: Location of the sample / Localización de la muestra L: Longitudinal / Longitudinal	B: Body / Cuerpo RT: Room Temperature / Temperatura Ambiente Obt: Obtained / Obtenido	Ss: Strip specimen / Rectangular EUL: Extension Under Load Method Y.S.: Yield Strength / Fluencia TMax: Transverse Maximum / Máximo Transversal	Ori: Orientation / Orientación UTS: Ultimate Tensile Strength / Resistencia LMin: Longitudinal Minimum / Mínimo Longitudinal Min: Minimum / Mínimo
Req. Max: Maximum Required / Máximo Requerido	TMin: Transverse Minimum / Mínimo Transversal		
LMax: Longitudinal Maximum / Máximo Longitudinal			

TECHNOLOGICAL TEST / ENSAYOS TECNOLÓGICOS

Heat N° Colada N°	Sample N° Muestra N°	Bend Test Ensayo de Curvado
742609	A4084/L	GOOD/BUENO
742609	C8634/L	GOOD / BUENO
742965	A4094/L	GOOD / BUENO
742965	A8031/L	GOOD / BUENO

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

MILL TEST CERTIFICATE	Number / Número	Page / Página:
	15023300	2 / 4
Date / Día: Jun 11, 2015		

Customer / Cliente: STOCK DISTRIBUIDORES		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 231918/01
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie. VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones. API 5L ED45		Steel Grade / Grado de acero. B/X42-L245/L290 PSL1		Ends / Extremos. PLAIN END LISO CORTE RECTO
Dimensions / Dimensiones. 1.90 X 0.200 INCH 48.30 X 5.10 MM	Schedule / Cédula 080	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad. 91 Pcs/pz	Nominal Weight / Peso Nominal 3.63 LB/FT 5.40 KG/M

CHEMICAL COMPOSITION / COMPOSICIÓN QUÍMICA

		Composition % / Composición %											
		C	Mn	Si	Cr	Mo	S	P	Ni	V	Cu	Nb	Ti
		X 100						X 1000					
Heat	H	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min
Colada	P	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min
Sample N°													
Muestra N°													
742609	H	17	89	24	7	4	2	11	140	2	140	1	2
A4084/L	P	17	90	25	7	4	4	11	150	1	140	1	1
A4085/L	P	17	91	25	7	4	4	11	150	1	140	1	1
C8634/L	P	17	90	26	7	4	3	10	150	2	140	2	2
C8635/L	P	17	90	26	7	4	3	10	150	2	140	2	1
742965	H	17	90	26	9	4	3	12	140	2	140	1	3
A4094/L	P	17	90	28	8	3	4	13	140	1	140	1	1
A4095/L	P	17	90	28	8	3	4	12	140	1	140	1	1
A8031/L	P	17	88	29	8	3	3	11	140	2	140	1	1
A8032/L	P	17	88	29	8	4	3	10	140	2	130	1	1

H: Heat / Colada P: Product / Producto Max: Maximum / Máximo Min: Minimum / Mínimo

SUPPLEMENTARY INFORMATION / INFORMACIÓN SUPLEMENTARIA

MANUFACTURED BY TENARIS SILCOTUB

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

MILL TEST CERTIFICATE

Number / Número Page / Página:

15023300

3 / 4

Date / Día: Jun 11, 2015

Customer / Cliente: STOCK DISTRIBUIDORES		Customer's Order / Orden Cliente - Item N°		Customer's Reference/Referencia del cliente		Manufacturer's Works Order N° / Confirmación de Venta 231918/01	
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA			Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION			Surface / Superficie. VARNISHED BARNIZADO	
Standard or Specification / Normas o especificaciones. API 5L ED45				Steel Grade / Grado de acero. B/X42-L245/L290 PSL1		Ends / Extremos. PLAIN END LISO CORTE RECTO	
Dimensions / Dimensiones. 1.90 X 0.200 INCH 48.30 X 5.10 MM		Schedule / Cédula 080	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS		Quantity / Cantidad. 91 Pcs/pz	Nominal Weight / Peso Nominal 3.63 LB/FT 5.40 KG/M	

SUPPLEMENTARY INFORMATION / INFORMACIÓN SUPLEMENTARIA

Standard: API 5L Year: 2012 Revision: Ed: Revision year: 45th
 Standard: ASTM A 53-12 Year: 2012
 Standard: ASTM A 106 Year: 2013
 Standard: ASME SA 53 Year: 2013
 Standard: ASME SA 106 Year: 2013
 Standard: NACE MR0175 Year: 2003
 STEEL GR. X42 PSL1, GR.B PSL1, ASTM ASME A/SA 106, A/SA 53
 INTERNALLY BARE, EXTERNALLY VARNISHED, WITH BLACK LACQUER.
 NONDESTRUCTIVE TEST-EDDY CURRENT ACC. TO ASTM E309,
 HOLE DIAMETER 1,1 mm max.: WITHOUT OBJECTIONS
 NONDESTRUCTIVE TEST EMI ACC. TO ASTM E 570: WITHOUT OBJECTIONS
 AFTER EMI INSPECTION, UNTESTED ENDS HAVE BEEN CUT OFF
 MATERIAL ACC. TO ASME II PART D TAB Y1
 MATERIAL ACC. TO NACE MR 01-75
 VISUAL AND DIMENSIONAL CONTROL HAS BEEN CARRIED OUT WITH SATISFACTORY RESULT
 STEEL IS FULLY KILLED AND PRODUCED BY ELECTRIC FURNACE TO A FINE GRAIN PRACTICE
 THE PRODUCT SUPPLIED IS IN COMPLIANCE WITH THE REQUIREMENTS OF THE ORDER.
 SUPERFICIAL HARDNESS (Max 235 0)
 HEAT SAMPLE SC LS SCALE VAL1 VAL2 VAL3
 742965 A4094/L AM B HBW 150.0 151.0 152.0
 742965 A8031/L AM B HBW 153.0 154.0 155.0
 742609 C8634/L AM B HBW 149.0 150.0 152.0
 742609 A4084/L AM B HBW 152.0 152.0 150.0

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.



Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.

MILL TEST CERTIFICATE	Number / Número 15023300	Page / Página: 4 / 4
Date / Día: Jun 11, 2015		

Customer / Cliente: STOCK DISTRIBUIDORES		Customer's Order / Orden Cliente - Item N°	Customer's Reference/Referencia del cliente	Manufacturer's Works Order N° / Confirmación de Venta 231918/01
Manufacture Process / Proceso de fabricación. SEAMLESS HOT ROLLED LAMINADO EN CALIENTE SIN COSTURA		Product Type / Tipo de producto. LINE PIPE SEAMLESS CONDUCCION		Surface / Superficie. VARNISHED BARNIZADO
Standard or Specification / Normas o especificaciones. API 5L ED45		Steel Grade / Grado de acero. B/X42-L245/L290 PSL1	Ends / Extremos. PLAIN END LISO CORTE RECTO	
Dimensions / Dimensiones. 1.90 X 0.200 INCH 48.30 X 5.10 MM	Schedule / Cédula 080	Length / Longitud. 19.70 / 21.30 FT 6.00 / 6.50 MTS	Quantity / Cantidad. 91 Pcs/pz	Nominal Weight / Peso Nominal 3.63 LB/FT 5.40 KG/M

SUPPLEMENTARY INFORMATION / INFORMACIÓN SUPLEMENTARIA

SC: SPECIMEN CONDITION
 AM: AS MANUFACTURED
 VAL: VALUE
 LS: LOCATION OF SAMPLE
 B: BODY
 HYDROSTATIC TEST: MPA 20.5 (5 SECONDS): SATISFACTORY
 TAMS REF: 642936

This is to certify that the product described here has been manufactured, sampled, tested, and inspected in accordance with purchaser order requirements. This certificate is not a declaration of origin nor may it be used as a declaration of origin.	Por el presente certificamos que el material aquí descrito ha sido fabricado, muestreado, ensayado e inspeccionado de acuerdo a los requisitos de su orden de compra. Este certificado no es ni puede ser usado, como una declaración de origen.
TENARIS QUALITY DEPARTMENT SIGNATURE	
 QUALITY CERTIFICATION DEPT DEPTO DE CERTIFICACIÓN DE CALIDAD Yael Garcia Hernandez	 CHIEF OF QUALITY CERTIFICATION DEPT RESPONSABLE DEL DEPTO DE CERTIFICACIÓN DE CALIDAD Rafael Gutierrez De Velasco Magallanes

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.	Este certificado se emite mediante sistema computarizado y es validado con firma electrónica. El certificado original posee impreso el logo Tenaris color verde. En caso de que el poseedor del certificado entregue una copia, deberá garantizar la conformidad con el original haciéndose responsable por cualquier uso ilegal o indebido. Cualquier alteración y/o falsificación estará sujeta a la ley.
---	---