WALWORTH Since 1842

Industrial de Valvulas, S.A de C.V.
Av. de La Industria Lote 16 Fracc. Industrial El Trebol
Tepotzotlan, Estado de México C.P. 54600

(Numero) Number **V064B5074**
(Fecha) Date **09/05/2008**

OUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598	- VALVE INSPECTION AND TESTING	API 6D	- PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
API 599	- METAL PLUG VALVES - FLANGED, THREADED AND WELDING	API 600	- STEEL GATE VALVES, FLANGED AND WELDING ENDS
ANSI B16-10	- FACE TO FACE AND END TO END DIMENSIONS OF VALVES	ANSI B16-11	- FORGED FITTINGS, SOCKET - WELDING AND THREADED
ANSI B16-34	- VALVES - FLANGED, THREADED AND WELDING ENDS	API 602	- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS
MSS-SP61	- PRESSURE TESTING OF STEEL VALVES		

Part No. **CB0203A1AAB**
(Código)
Description **2" Fig. 8612 F A105, TH0000B**
Descripción **STEEL BALL VALVE**
(VALVULA ESFERA DE ACERO)

MANUFACTURED TO MEET NACE MR-01-75 REQUIREMENTS FIRE TEST API 6FA, API 07. REV 2003 (VALVULA SERVICIO NACE MR-01-75/ISO 5156 ED 2003
PRUEBA DE FUEGO API 6FA, API 607

)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO) 1	SIDE (LADO) 2
HYDROSTATIC (PSI) (HIDROSTATICA)	2225		1630	1630
PNEUMATIC (PSI) (NEUMATICA)			80	80

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) / COMPOSICIÓN QUIMICA (%) C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	MECHANICAL TESTS (PROP. MECANICAS) TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BALL BOLA	B069	ASTM A-105N	0.205	0.760	0.010	0.002	0.200	0.080	0.240	0.010	0.260	0.006		76.20	44.99	36	46	162
BODY CUERPO	063-2780	ASTM A-105N	0.200	0.780	0.021	0.021	0.210	0.040	0.040	0.001	0.040	0.001		77.79	53.70	38	48	168
END1 EXTREMO1	506-575	ASTM A-105N	0.210	0.760	0.021	0.021	0.220	0.030	0.030	0.001	0.040	0.001		77.07	50.80	38	45	158
END2 EXTREMO2	506-575	ASTM A-105N	0.210	0.760	0.021	0.021	0.220	0.030	0.030	0.001	0.040	0.001		77.07	50.80	38	45	158

FAC10-21 REV "3"

CERTIFICADO POR:
ASEGURAMIENTO DE CALIDAD

CERTIFIED BY :
QUALITY ASSURANCE

SANDRA RUIZ