



WALWORTH®

Industrial de Válvulas, S.A. de C.V.
Av. de la Industria Lote 16 Fracc. Industrial el Trébol
Tepetzotlán, Estado de México C.P. 54600

(NUMERO) NUMBER:

(FECHA) DATE:

V06C26011
31/10/2006

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED
ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE
OF THE FOLLOWING STANDARDS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRUBADO
DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS
EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED AND WELDING ENDS
- ANSI B16 .10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16 .34 - VALVES - FLANGED, THREADED, AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

PART. No.: 25780P
(CODIGO)

DESCRIPTION: 2" FIG. 5202 F UT WCB, API TRIM No.8
(DESCRIPCION) CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL

(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)
(FUGITIVAS A 50 PPM'S MAX)
()

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)											MECHANICAL TESTS (PROP. MECANICAS)				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
			BODY (CUERPO)	WH13910	A-216/WCB	0.212	0.893	0.022	0.017	0.470	0.040	0.080	0.020	0.020	0.001	76.12	45.53	28.0
Normalized to 920.00 OC.. Cooled in air. (Normalizado a 920.00 OC.. Enfriado en aire.)																		
BONNET COVER (BONETE TAPA)	WH15487	A-216/WCB	0.200	0.963	0.021	0.010	0.489	0.020	0.030	0.043	0.005	0.003	77.48	47.56	29.6	58.0	154	
Normalized to 930.00 OC.. Cooled in air. (Normalizado a 930.00 OC.. Enfriado en aire.)																		
WEDGE DISK (DISCO)	WH91063	-217/CA15	0.125	0.578	0.021	0.018	0.699	0.084	13.390	0.030	0.084	0.001	100.20	70.04	24.0	45.0	306	
Normalized to 970.00 OC.. Cooled in air. (Normalizado a 970.00 OC.. Enfriado en aire.)																		

CERTIFIED BY: _____
QUALITY ASSURANCE
CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD