

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)
ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO
WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:
(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICION.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES
- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. CB0203A1AAB
(Codigo) **2" Fig. 8612 F A105, TH0000B**
Description **STEEL BALL VALVE**
(VALVULA ESFERA DE ACERO)

MANUFACTURED TO MEET NACE MR-01-75 REQUIREMENTS FIRE TEST API 6FA, API 607, REV 2003 (VALVULA SERVICIO NACE MR-01-75 REQUISITOS FUE TEST API 6FA, API 607, REV 2003 (VALVULA PRUEBA DE FUEGO API 6FA, API 607

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	2225	1630	1630
PNEUMATIC (PSI) (NEUMATICA)		80	80

MECHANICAL TESTS (PROP. MECANICAS)

ITEM (PARTES)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											MECHANICAL TESTS (PROP. MECANICAS)				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS (KPSI CVMG)	YIELD (KPSI 1ST)	ELG (%) 2ND	RED (%) 3RD	BHN AVG
BALL BOLA	B069	ASTM A-105N	0.205	0.760	0.010	0.002	0.200	0.080	0.240	0.010	0.260	0.006	76.20	44.99	36	46	162	
BODY CUERPO	07-2-111	ASTM A-105N	0.200	0.830	0.015	0.006	0.250	0.100	0.110	0.010	0.160	0.001	72.86	54.43	33	72	160	
END1 EXTREMO1	07-2-114	ASTM A-105N	0.190	0.860	0.017	0.005	0.240	0.090	0.150	0.010	0.160	0.001	73.29	50.94	33	58	152	
END2 EXTREMO2	07-2-114	ASTM A-105N	0.190	0.860	0.017	0.005	0.240	0.090	0.150	0.010	0.160	0.001	73.29	50.94	33	58	152	