WALWORTH®

Industrial de Válvulas, S.A. de C.V.
Av. de la Industria Lote 16 Fracc. Industrial el Trébol
Tepotzotlán, Estado de México C.P. 54600

(NUMERO) **NUMBER:** V07C11142
(FECHA) **DATE:** 02/10/2007

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE
ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARS:

CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES

API 6D	- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
API 600	- STEEL GATE VALVES - FLANGED AND BUT-WELDING ENDS
API 598	- VALVE INSPECTION AND TESTING
API 599	- METAL PLUG VALVES - FLANGED AND WELDING ENDS
ANSI B16 .10	- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
ANSI B16 .34	- VALVES - FLANGED, THREADED, AND WELDING ENDS
MSS-SP61	- PRESSURE TESTING OF STEEL VALVES

PART. No.: (CODIGO) 25787P

DESCRIPTION: (DESCRIPCION) 4" FIG. 5206 F UT WCB, API TRIM No.8
CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)
VALVE WITH LOW EMISSION CONTROL (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES)
(FUGITIVAS A 50 PPM'S MAX)
( )

PRESSURE TESTS (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK SEAT	SIDE (LADO) 1	SIDE (LADO) 2
HYDROSTATIC (PSI) (HIDROSTATICA)	1125	1125	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

( )

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
		CHEMICAL COMPOSITION (%) (COMPOSICION QUIMICA)												MECHANICAL TESTS (PROP. MECANICAS)				
BODY (CUERPO)	WH14541	A-216/WCB	0.199	0.848	0.022	0.014	0.450	0.033	0.031	0.016	0.021	0.010		71.19	43.21	30.5	46.0	152
Normalizated to 930.00 ºC.. Cooled in air. (Normalizado a 930.00 ºC.. Enfriado en aire.)																		
BONNET COVER (BONETE TAPA)	WH14548	A-216/WCB	0.193	0.863	0.022	0.015	0.522	0.031	0.037	0.015	0.015	0.010		71.63	40.74	35.6	51.0	153
Normalizated to 930.00 ºC.. Cooled in air. (Normalizado a 930.00 ºC.. Enfriado en aire.)																		
WEDGE DISK (DISCO)	WH81128	-217/CA15	0.128	0.628	0.036	0.018	0.763	0.132	13.400	0.048	0.014	0.001		100.63	74.38	25.0	45.0	284
Normalizated to 970.00 ºC.. Cooled in air. (Normalizado a 970.00 ºC.. Enfriado en aire.)																		

CERTIFIED BY:
CERTIFICADO POR: QUALITY ASSURANCE / ASEGURAMIENTO DE CALIDAD

FAC10-21 REV "1"