



WALWORTH
Since 1842

Industrial de Valvulas, S.A de C.V.
Av. de La Industria Lote 16 Fracc. Industrial El Trebol
Tepic, Jalisco, Estado de Mexico C.P. 54600

(Numero) Number
(Fecha) Date

V07C22177
10/12/2007

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES
- API 6D - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. AC022A05MAB

(Codigo) 2 1/2" Fig. 5206 F HF WCB, API TRIM No. 5 790000K

Description CAST STEEL GATE VALVE
(VALVULA COMPUERTA DE ACERO FUNDIDO)
MANUFACTURED TO MEET NACE MR-01-75-2003 REQUIREMENTS AND LOW FUGITIVE EMISSIONS CONTROL.
(VALVULA SERVICIO NACE MR-01-75 *Y CONTROL DE EMISIONES FUGITIVAS 50 PPM'S)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	1125	1125	NA	NA
PNEUMATIC (PSI) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICION QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN ₆₀	YIELD KPSI 1ST	ELG %	RED %	BHN AVG
BONNET BONETE	WH16060	ASTM A-216/WCB	0.188	0.964	0.028	0.009	0.456	0.044	0.052	0.012	0.031	0.004		80.04	42.92	37	43	157
BODY CUERPO	WH15838	ASTM A-216/WCB	0.189	0.960	0.025	0.023	0.496	0.046	0.047	0.017	0.006	0.001		83.95	49.01	32	52	150
WEDGE DISCO	D0620	ASTM A-216/WCB	0.180	0.820	0.023	0.020	0.440	0.031	0.069	0.026	0.038	0.002		75.26	47.13	27	46	169

Normalized to (Normalizado a) 920 °C

Cooled in air (Cooled in air: (Enfri)

Sandra Ruiz