

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES)

API 598
 API 599
 ANSI B16-10
 ANSI B16-34
 MSS-SP61

- VALVE INSPECTION AND TESTING
 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
 - VALVES - FLANGED, THREADED AND WELDING ENDS
 - PRESSURE TESTING OF STEEL VALVES

API 6D
 API 600
 ANSI B16-11
 API 602

- PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
 - COMPACT STEEL GATE VALVES - FLANGED, THREADED,
 WELDING AND EXTENDED - BODY ENDS

Part No. **AC041A08MAA**

(Codigo) **4" Fig. 5202 F UT WCB, API TRIM No.8 8300000**

Description

CAST STEEL GATE VALVE
 (VALVULA COMPUERTA DE ACERO FUNDIDO)
 VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICIÓN QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG				
BONNET BONETE	WHZ0957	ASTM A-216/WCB	0.219	0.908	0.025	0.020	0.438	0.042	0.040	0.027	0.020	0.005		81.06	50.90	30	57	157				
BODY CUERPO	WHZ0539	ASTM A-216/WCB	0.214	0.989	0.025	0.016	Temper to (Temple a) 930 °C 0.469	0.044	0.028	0.021	0.040	0.003		76.85	49.88	33	58	150				
WEDGE DISCO	WH81117	ASTM A-217/CA15	0.130	0.519	0.029	0.020	0.459	0.088	12.690	0.021	0.010	0.001	0.000	91.06	74.82	28	45	287				
			Normalizado a (Normalized to) 970 °C											Temple a (Temper to) 630 °C					Enfriado en aire. (Enfriado en aire. (C)			