



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepozotlan, Estado de México C.P. 54600

(Numero) Number V07C32057
 (Fecha) Date 28/09/2007

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AC061A08MAA**

(Codigo) **6" Fig. 5202 F UT WCB, API TRIM No.8 8300000**

Description **CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)**
VALVE WITH LOW EMISSION CONTROL (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSD) (HIDROSTATICA)	450	450	N/A	N/A
PNEUMATIC (PSD) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	COMPOSICIÓN QUÍMICA (%)																
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS (KPSI CVN@)	YIELD (KPSI 1ST)	ELG (% 2ND)	RED (% 3RD)	BHN AVG	
BONNET BONETE	WH17100	ASTM A-216/WCB	0.189	0.874	0.021	0.010	0.400	0.045	0.044	0.022	0.005	0.001		78.59	50.31	32	60	161	
BODY CUERPO	WH17652	ASTM A-216/WCB	Normalized to (Normalizado a) 930 °C 0.181	0.938	0.026	0.016	Temper to (Temple a) 650 °C 0.519	0.022	0.030	0.004	0.023	0.004		85.11	53.21	29	54	150	
WEDGE DISCO	WH16136	ASTM A-217/CA15	Normalized to (Normalizado a) 930 °C 0.117	0.693	0.025	0.014	Temper to (Temple a) 650 °C 0.648	0.105	13.278	0.016	0.031	0.001		101.06	70.03	24	41	287	
			Normalized a (Normalizado to) 970 °C				Temple a (Temper to) 630 °C												

FACIO-21 REV "2"

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD

CERTIFIED BY: QUALITY ASSURANCE


 Sandra Rutz