



**WALWORTH**  
Since 1842

Industrial de Valvulas, S.A de C.V.  
Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
Tepic, Jalisco, Estado de Mexico C.P. 54600

(Numero) Number  
(Fecha) Date

V07C33495  
14/11/2007

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:  
(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRUBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

API 598  
API 599  
ANSI B16-10  
ANSI B16-34  
MSS-SP61

- VALVE INSPECTION AND TESTING
- METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- VALVES - FLANGED, THREADED AND WELDING ENDS
- PRESSURE TESTING OF STEEL VALVES

API 6D  
API 600  
ANSI B16-11  
API 602

- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- STEEL GATE VALVES, FLANGED AND WELDING ENDS
- FORGED FITTINGS, SOCKET - WELDING AND THREADED
- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. AC021A08MAA  
(Codigo)

Description 2 1/2" Fig. 5202 F UT WCB, API TRIM No.8 8300000

CAST STEEL GATE VALVE  
(VALVULA COMPUERTA DE ACERO FUNDIDO)  
VALVE WITH LOW EMISSION CONTROL  
(VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A N A
PNEUMATIC (PSI) (NEUMATICA)			80 80

### MECHANICAL TESTS (PROP. MECANICAS)

### CHEMICAL COMPOSITION (%)

### COMPOSICIÓN QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN <sub>60</sub>	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BONNET BONETE	WH13258	ASTM A-216/WCB	0.197	0.956	0.029	0.022	0.496	0.040	0.020	0.010	0.050	0.001	0.000	74.24	46.83	28	49	162
BODY CUERPO	WH15198	ASTM A-216/WCB	0.213	0.897	0.030	0.020	0.517	0.040	0.020	0.030	0.010	0.001		75.55	45.39	26	48	164
WEDGE DISCO	1A945	ASTM A-216/WCB	0.241	0.694	0.013	0.009	0.598	0.396	0.190	0.001	0.093	0.004		78.63	39.65	31	41	159

Normalized to (Normalizado a) 920 °C  
Cooled in air (Cooled in air. (Enfr)

Normalized to (Normalizado a) 930 °C  
Temper to (Temple a) 650 °C

Cooled in air (Cooled in air. (Enfr)

Cooled in air (Cooled in air. (Enfr)