

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. AC031A08MAA

(Código) **3" Fig. 5202 F UT WCB, API TRIM No.8 7900000**

Description **CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)**
MANUFACTURED TO MEET NACE MR-01-75-2003 REQUIREMEN *TS AND LOW FUGITIVE EMISSIONS CONTROL.
(VALVULA SERVICIO NACE MR-01-75 *Y CONTROL DE EMISIONES FUGITIVAS 50 PPM'S)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAL)	SIDE (LADO)	
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	1	2
PNEUMATIC (PSI) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICIÓN QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS (KPSI CVN@)	YIELD (KPSI 1ST)	ELG (%) 2ND	RED (%) 3RD	BHN AVG
BONNET BONETE	WH18374	ASTM A-216/WCB	0.193	0.878	0.031	0.022	0.404	0.035	0.049	0.021	0.006	0.003		72.79	43.79	33	55	160
BODY CUERPO	WH18780	ASTM A-216/WCB	0.208	0.918	0.025	0.017	0.180	0.039	0.042	0.015	0.016	0.004		80.62	51.48	34	54	152
WEDGE DISCO	WH81491	ASTM A-217/CA15	0.134	0.620	0.024	0.019	0.650	0.096	13.400	0.023	0.024	0.018		99.18	73.52	23	39	289

Normalizado a (Normalized to) 930 °C
Normalizado a (Normalized to) 930 °C
Normalizado a (Normalized to) 930 °C
Normalizado a (Normalized to) 970 °C