



Industrial de Valvulas, S.A de C.V.  
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
 Tepozotlan, Estado de Mexico C.P. 54600

(Numero) Number V07C37991  
 (Fecha) Date 10/12/2007

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:  
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- VALVE INSPECTION AND TESTING
- METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- VALVES - FLANGED, THREADED AND WELDING ENDS
- PRESSURE TESTING OF STEEL VALVES
- PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
- STEEL GATE VALVES, FLANGED AND WELDING ENDS
- FORGED FITTINGS, SOCKET - WELDING AND THREADED
- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. AC011A08MAB

(Codigo) 2" Fig. 5202 F UT WCB, API TRIM No.8 830000K

Description  
 CAST STEEL GATE VALVE  
 (VALVULA COMPUERTA DE ACERO FUNDIDO)  
 VALVE WITH LOW EMISSION CONTROL  
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

#### MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)	COMPOSICIÓN QUÍMICA (%)					TENS	YIELD	ELG	RED	BHN
--------------------------	-------------------------	--	--	--	--	------	-------	-----	-----	-----

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BONNET	WH25079	ASTM A-216/WCB	0.195	0.852	0.028	0.017	0.481	0.020	0.030	0.005	0.018	0.002		77.29	47.85	31	46	152
BONNET			Normalized to (Normalizado a) 930 °C															
BODY	WH17648	ASTM A-216/WCB	0.192	0.937	0.024	0.016	0.444	0.026	0.022	0.040	0.026	0.003		80.33	51.33	29	54	152
CUERPO			Normalized to (Normalizado a) 920 °C															
WEDGE	D3258	ASTM A-217/CA15	0.120	0.760	0.015	0.013	1.100	0.250	12.220	0.046	0.030	0.001		99.62	70.91	29	42	275
DISCO			Normalized to (Normalizado to) 970 °C															
			Temple a (Temper to) 630 °C															
			Enfriado en aire (Enfriado en aire: (C)															

FACIO-21 REV "2"

CERTIFICADO POR:  
 ASEGURAMIENTO DE CALIDAD

CERTIFIED BY:  
 QUALITY ASSURANCE

Sandra Ruiz