



**WALWORTH**<sup>®</sup>

Since 1842

Industrial de Valvulas, S.A de C.V.  
Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
Tepic, Jalisco, Estado de Mexico C.P. 54600

(Numero) Number  
(Fecha) Date

V07R6918  
26/11/2007

# QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

## ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:  
(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES
- API 6D - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AR011A08MAA**

(Codigo)

**2" Fig. 5341 F UT WCB, API TRIM No.8 8300000**

Description

**CAST STEEL SWING CHECK VALVE**  
**(VALVULA RETENCION TIPO COLUMPIO DE ACERO FUNDIDO)**

VALVE WITH LOW EMISSION CONTROL  
(VALVULA SIMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAL)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	N A	315	N A
PNEUMATIC (PSI) (NEUMATICA)			N A	N A

### MECHANICAL TESTS (PROP. MECANICAS)

### CHEMICAL COMPOSITION (%)

### COMPOSICION QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BODY CUERPO	WH10005	ASTM A-216/WCB	0.202	0.902	0.031	0.018	0.481	0.009	0.034	0.006	0.021	0.006	0.000	73.66	43.93	29	48	156
WEDGE DISCO	HD3696	ASTM A-217/CA15	0.100	0.740	0.032	0.011	0.930	0.850	12.660	0.012	0.052	0.001		100.19	69.45	24	47	271
COVER TAPA	WH19153	ASTM A-216/WCB	0.189	0.986	0.019	0.010	0.402	0.044	0.084	0.014	0.026	0.001		73.23	44.23	30	47	158

Normalized to (Normalizado a) 930 °C

Cooled in air (Cooled in air: (Enfr)

  
Sandra Ruiz