

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. **AR011A08MAA**

(Codigo) **2" Fig. 5341 F UT WCB, API TRIM No.8 8300000**

Description **CAST STEEL SWING CHECK VALVE
 (VALVULA RETENCIÓN TIPO COLUMPIO DE ACERO FUNDIDO)
 VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)**

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEÑAL)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	N A	315
PNEUMATIC (PSI) (NEUMATICA)		N A	N A

MECHANICAL TESTS (PROP. MECANICAS)

ITEM (PARTS)	HEAT No. (COLADA)	MATERIAL (ASTM)	CHEMICAL COMPOSITION (%)											MECHANICAL TESTS (PROP. MECANICAS)				
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	W	TENS KPSI CVN@	YIELD KPSI 1ST	ELG %	RED %	BHN AVG
BODY CUERPO	WH6422	ASTM A-216/WCB	0.200	0.950	0.020	0.020	0.473	0.020	0.030	0.010	0.040	0.001	0.000	74.96	45.82	25	48	168
WEDGE DISCO	HD3695	ASTM A-217/CA15	0.130	0.710	0.023	0.021	0.890	0.790	12.760	0.029	0.015	0.001		100.05	69.45	27	45	277
COVER TAPA	WH19153	ASTM A-216/WCB	0.189	0.986	0.019	0.010	0.402	0.044	0.084	0.014	0.026	0.001		73.23	44.23	30	47	158
			Normalized to (Normalizado a) 930 °C											Cooled in air: (Enfriado en aire: (C))				

Sandra Ruiz