

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598 - VALVE INSPECTION AND TESTING
 API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
 ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
 ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
 MSS-SP61 - PRESSURE TESTING OF STEEL VALVES

API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
 API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
 ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
 API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. AR061A08MAB830000G
(Código)
Description **6" Fig. 5341 F UT WCB, API TRIM No.8 830000**
Descripción **CAST STEEL SWING CHECK VALVE 150 CLASS**
(VALVULA RETENCIÓN TIPO COLUMPIO DE ACERO FUNDIDO CLASE 150)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

| PRESSURE TEST (PRUEBAS DE PRESION) | SHELL (CASCO) | BACK (SEAT) | SIDE (LADO) | |
|---------------------------------------|------------------|----------------|----------------|-----|
| | | | 1 | 2 |
| HYDROSTATIC (PSI) (HIDROSTATICA) | 450 | N A | 315 | N A |
| PNEUMATIC (PSI) (NEUMATICA) | | | N A | N A |

MECHANICAL TESTS (PROP. MECANICAS)

| CHEMICAL COMPOSITION (%) | | | COMPOSICIÓN QUIMICA (%) | | | | | | | | | | TENS YIELD ELG RED BHN | | | | | | |
|--------------------------|----------------------|--------------------|-----------------------------------|-------|-------|-------|--------------------------|-------|-------|-------|------------------------------------|-------|------------------------|--------------|-------------|----------|----------|-----|-----|
| ITEM (PARTE) | HEAT No. (COLADA) | MATERIAL (ASTM) | C | Mn | P | S | Si | Ni | Cr | Mo | Cu | V | Cb | KPSI CVN@ | KPSI 1ST | % 2ND | % 3RD | AVG | |
| BODY CUERPO | 12839 | ASTM A-216/WCB | 0.190 | 0.730 | 0.022 | 0.018 | 0.390 | 0.050 | 0.050 | 0.050 | 0.040 | 0.010 | | 73.08 | 40.60 | 31 | 42 | 156 | |
| COVER TAPA | 12840 | ASTM A-216/WCB | Normalized to (Normalizado a) 920 | | | | Temper to (Temple a) 650 | | | | Cooled in air. (Enfriado en aire.) | | | | 74.53 | 40.45 | 32 | 41 | 160 |
| WEDGE DISCO | 12838 | ASTM A-216/WCB | Normalized to (Normalizado a) 920 | | | | Temper to (Temple a) 650 | | | | Cooled in air. (Enfriado en aire.) | | | | 73.51 | 41.18 | 30 | 39 | 153 |
| | | | Normalized to (Normalizado a) 920 | | | | Temper to (Temple a) 650 | | | | Cooled in air. (Enfriado en aire.) | | | | | | | | |

CERTIFICADO POR: ASEGURAMIENTO DE CALIDAD
 CERTIFIED BY: QUALITY ASSURANCE



Jessica Garcia