



Industrial de Valvulas, S.A de C.V.  
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol  
 Tepozotlan, Estado de México C.P. 54600

(Numero) Number V08C11016  
 (Fecha) Date 01/02/2008

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:  
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES)

- VALVE INSPECTION AND TESTING
- METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- VALVES - FLANGED, THREADED AND WELDING ENDS
- PRESSURE TESTING OF STEEL VALVES
- PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
- STEEL GATE VALVES, FLANGED AND WELDING ENDS
- FORGED FITTINGS, SOCKET - WELDING AND THREADED
- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AC022A08MAB**

(Codigo) **2 1/2" Fig. 5206 F UT WCB, API TRIM No.8 830000M**

Description **CAST STEEL GATE VALVE (VALVULA COMPUERTA DE ACERO FUNDIDO)**

VALVE WITH LOW EMISSION CONTROL (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAL)	SIDE (LADO)
HYDROSTATIC (PSID) (HIDROSTATICA)	1125	1125	N A N A
PNEUMATIC (PSID) (NEUMATICA)			80 80

### MECHANICAL TESTS (PROP. MECANICAS)

### CHEMICAL COMPOSITION (%) COMPOSICIÓN QUIMICA (%)

ITEM (PARTES)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS (KPSI CVN@)	YIELD (KPSI 1ST)	ELG (% 2ND)	RED (% 3RD)	BHN (AVG)
BONNET (BOÑETE)	WH17093	ASTM A-216/WCB	0.188	0.979	0.025	0.020	0.425	0.043	0.043	0.015	0.005	0.001		83.52	41.47	31	62	160
BODY (CUERPO)	WH19891	ASTM A-216/WCB	0.206	0.880	0.029	0.023	0.478	0.040	0.061	0.024	0.018	0.004		74.39	42.92	34	53	160
WEDGE (DISCO)	D3988	ASTM A-216/WCB	0.200	0.830	0.018	0.016	0.440	0.032	0.093	0.027	0.026	0.003		75.54	47.12	24	47	171

FACIO-21 REV 2"

CERTIFICADO POR ASEGURAMIENTO DE CALIDAD

CERTIFIED BY :

QUALITY ASSURANCE Sandra Ruiz