



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepozotlan, Estado de Mexico C.P. 54600

(Numero) Number
 (Fecha) Date

V08C11029
 05/02/2008

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- VALVE INSPECTION AND TESTING
- METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- VALVES - FLANGED, THREADED AND WELDING ENDS
- PRESSURE TESTING OF STEEL VALVES

- API 6D
- API 600
- ANSI B16-11
- API 602
- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- STEEL GATE VALVES, FLANGED AND WELDING ENDS
- FORGED FITTINGS, SOCKET - WELDING AND THREADED
- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. AC022A08MAB

(Codigo) 2 1/2" Fig. 5206 F UT WCB, API TRIM No.8 830000M

Description

CAST STEEL GATE VALVE
 (VALVULA COMPUERTA DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
HYDROSTATIC (PSI) (HIDROSTATICA)	1125	1125	1	2
PNEUMATIC (PSID) (NEUMATICA)			80	80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICIÓN QUÍMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	SI	NI	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BONNET	WH19929	ASTM A-216/WCB	0.213	0.883	0.019	0.017	0.523	0.044	0.040	0.020	0.029	0.004	0.004	84.83	54.67	30	45	150
BONNET	WH19927	ASTM A-216/WCB	0.191	0.948	0.027	0.018	0.456	0.037	0.072	0.020	0.008	0.003	0.003	79.46	49.59	29	56	158
WEDGE	D3665	ASTM A-217/CA15	0.090	0.780	0.010	0.018	0.910	0.880	13.000	0.020	0.019	0.001	0.001	98.46	71.34	27	46	278

Normalizado a (Normalizado a) 920 °C
 Normalizado a (Normalizado a) 920 °C
 Normalizado a (Normalizado a) 920 °C
 Normalizado a (Normalizado a) 955 °C
 Temple a (Temper to) 650 °C
 Temple a (Temper to) 650 °C
 Enfriado en aire (Enfriado en aire. (C)

CERTIFICADO POR:
 ASEGURAMIENTO DE CALIDAD

CERTIFIED BY:
 QUALITY ASSURANCE

Sandra Ruiz