

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. AC041A08MAB
(Código) 4" Fig. 5202 F UT WCB, API TRIM No.8 830000K
Description CAST STEEL GATE VALVE
(VALVULA COMPUERTA DE ACERO FUNDIDO)
 VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A N A
PNEUMATIC (PSI) (NEUMATICA)			80 80

MECHANICAL TESTS (PROP. MECANICAS)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	COMPOSICIÓN QUIMICA (%)										MECHANICAL TESTS (PROP. MECANICAS)					
			C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN(a)	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
BONNET (BONETE)	WH26089	ASTM A-216/WCB	0.217	0.968	0.034	0.019	0.436	0.019	0.034	0.024	0.047	0.018		75.25	45.53	25	49	159
			Normalized to (Normalized a) 920 °C	0.215	0.968	0.030	0.014	0.533	0.006	0.058	0.010	0.028	0.006		75.54	44.66	24	44
BODY (CUERPO)	WH25753	ASTM A-216/WCB	0.090	0.770	0.015	0.030	0.810	0.410	12.420	0.071	0.028	0.005		99.18	70.90	25	47	273
			Normalized to (Normalized a) 920 °C	0.090	0.770	0.015	0.030	0.810	0.410	12.420	0.071	0.028	0.005		99.18	70.90	25	47
WEDGE (DISCO)	D9653.	ASTM A-217/CA15	Temple a (Temper to) 630 °C										Enfriado en aire. (Enfriado en aire. (C)					



Sandra Ruiz