

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)
 ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. **AC011A08MAB**
 (Código) **2" Fig. 5202 F UT WCB, API TRIM No.8 830000K**
 Description **CAST STEEL GATE VALVE**
 Descripción **(VALVULA COMPUERTA DE ACERO FUNDIDO)**

VALVE WITH LOW EMISSION CONTROL (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	1 N A
PNEUMATIC (PSI) (NEUMATICA)			80 N A

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)		COMPOSICIÓN QUIMICA (%)										TENS	YIELD	ELG	RED	BHN		
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@a	KPSI 1ST	% 2ND	% 3RD	AVG
BONNET	WHZ6058	ASTM A-216/WCB	0.194	0.960	0.031	0.007	0.429	0.005	0.062	0.018	0.025	0.015		74.24	45.68	28	47	158
BONNET			Normalized to (Normalized a) 930 °C															
BODY	WHZ2492	ASTM A-216/WCB	0.206	0.857	0.028	0.009	0.527	0.040	0.004	0.015	0.037	0.004		74.96	44.37	26	48	168
CUERPO			Normalized to (Normalized a) 930 °C															
WEDGE	D0013	ASTM A-217/CA15	0.110	0.780	0.019	0.024	0.960	0.310	12.410	0.038	0.051	0.004		97.73	70.16	25	45	275
DISCO			Normalized a (Normalized to) 970 °C															
			Temple a (Temper to) 630 °C															
			Enfriado en aire. (Enfriado en aire. (C)															



Sandra Ruiz