



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepotzotlan, Estado de Mexico C.P. 54600

(Numero) Number V08C3056
 (Fecha) Date 01/02/2008

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS: ESTANDARES)
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES.)

- VALVE INSPECTION AND TESTING
- METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- VALVES - FLANGED, THREADED AND WELDING ENDS
- PRESSURE TESTING OF STEEL VALVES
- PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK
- STEEL GATE VALVES, FLANGED AND WELDING ENDS
- FORGED FITTINGS, SOCKET - WELDING AND THREADED
- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AC062A08MAB**
 (Codigo) **6" Fig. 5206 F UT WCB, API TRIM No.8 830000M**
 Description **CAST STEEL GATE VALVE**
(VALVULA COMPUERTA DE ACERO FUNDIDO)
 VALVE WITH LOW EMISSION CONTROL.
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGTIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	1125	1125	N A	N A
PNEUMATIC (PSI) (PNEUMATICA)			80	80

CHEMICAL COMPOSITION (%)

COMPOSICIÓN QUÍMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KSI CVN@	YIELD KSI 1ST	ELG %	RED %	BHN AVG
BONNET	WH18150	ASTM A-216/WCB	0.207	0.997	0.033	0.024	0.515	0.058	0.045	0.032	0.038	0.006		74.82	47.99	30	43	157
BODY	WH21919	ASTM A-216/WCB	0.214	0.890	0.028	0.017	0.410	0.060	0.050	0.047	0.033	0.006		78.59	46.26	30	48	157
WEDGE	D3929	ASTM A-217/CA15	0.110	0.730	0.023	0.020	0.940	0.600	12.620	0.029	0.075	0.002		99.03	69.89	27	44	275
DISCO			Normalizado a (Normalized to) 970 °C															

MECHANICAL TESTS (PROP. MECANICAS)

CERTIFICADO POR:
 ASEGURAMIENTO DE CALIDAD

CERTIFIED BY:
 QUALITY ASSURANCE

 Sandra Ruiz