



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepic/Jalisco, Estado de Mexico C.P. 54600

(Numero) Number V08G2103
 (Fecha) Date 15/02/2008

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES)

- | | | | |
|-------------|---|-------------|---|
| API 598 | - VALVE INSPECTION AND TESTING | API 6D | - PIPELINE VALVES - GATE, PLUG, BALL ANF CHECK |
| API 599 | - METAL PLUG VALVES - FLANGED, THREADED AND WELDING | API 600 | - STEEL GATE VALVES, FLANGED AND WELDING ENDS |
| ANSI B16-10 | - FACE TO FACE AND END TO END DIMENSIONS OF VALVES | ANSI B16-11 | - FORGED FITTINGS, SOCKET - WELDING AND THREADED |
| ANSI B16-34 | - VALVES - FLANGED, THREADED AND WELDING ENDS | API 602 | - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
| MSS-SP61 | - PRESSURE TESTING OF STEEL VALVES | | |

Part No. AG021A08MAA
 (Codigo) **2 1/2" Fig. 5275 F UT WCB, API TRIM No.8 8300000**
 Description **CAST STEEL GLOBE VALVE**
(VALVULA GLOBO DE ACERO FUNDIDO)
 VALVE WITH LOW EMISSION CONTROL
 (VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGITIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	315
PNEUMATIC (PSI) (NEUMATICA)			80
			N A

CHEMICAL COMPOSITION (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	SI	NI	Cr	Mo	Cu	V	Cb	TENS (KPSI) (CIN/6)	YIELD (KPSI) (1ST)	ELG (%) (2ND)	RED (%) (3RD)	BHN (AVG)
BONNET	311031	ASTM A-216/WCB	0.240	0.780	0.014	0.008	0.520	0.030	0.140	0.001	0.000	0.000		82.28	42.63	27	45	163
BONETE			Normalized to (Normalizado a) 930 °C															
BODY	874A396	ASTM A-216/WCB	0.200	0.720	0.020	0.036	0.400	0.130	0.160	0.050	0.126	0.003		76.93	47.17	24	45	156
CUERPO			Normalized to (Normalizado a) 930 °C															
WEDGE	676-07	ASTM A-276 GR 410	0.117	0.490	0.024	0.004	0.499	0.203	12.730	0.034	0.202			74.00	56.00	35	50	156
DISCO			Normalized to (Normalizado a) 930 °C															

MECHANICAL TESTS (PROP. MECANICAS)


 Sandra Ruiz