



Industrial de Valvulas, S.A de C.V.
 Av. de La Industria Lote 16 Fracc. Industrial El Trebol
 Tepic, Jalisco, Estado de Mexico C.P. 54600

(Numero) Number
 (Fecha) Date

V08G2151
 04/03/2008

QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)
 ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:
 (CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICION.)

- API 598 - VALVE INSPECTION AND TESTING
- API 599 - METAL PLUG VALVES - FLANGED, THREADED AND WELDING
- ANSI B16-10 - FACE TO FACE AND END TO END DIMENSIONS OF VALVES
- ANSI B16-34 - VALVES - FLANGED, THREADED AND WELDING ENDS
- MSS-SP61 - PRESSURE TESTING OF STEEL VALVES
- API 6D - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
- API 600 - STEEL GATE VALVES, FLANGED AND WELDING ENDS
- ANSI B16-11 - FORGED FITTINGS, SOCKET - WELDING AND THREADED
- API 602 - COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS

Part No. **AG031A08MAA**

(Codigo) **3" Fig. 5275 F UT WCB, API TRIM No.8 8300000**

Description **CAST STEEL GLOBE VALVE**

(VALVULA GLOBO DE ACERO FUNDIDO)

VALVE WITH LOW EMISSION CONTROL.
 VALVULA SUMINISTRADA CON CONTROL DE EMISIONES FUGTIVAS A 50 PPM'S MAX)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	315
PNEUMATIC (PSI) (NEUMATICA)			80

MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)

COMPOSICION QUIMICA (%)

ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Min	P	S	SI	NI	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG %	RED %	BHN AVG
BONNET BONETE	XS412	ASTM A-216/WCB	0.230	0.810	0.029	0.021	0.380	0.018	0.110	0.071				75.11	46.40	25	41	170
BODY CUERPO	WH13631	ASTM A-216/WCB	0.186	0.873	0.029	0.022	Tempor to (Temple a) 650 °C 0.450	0.050	0.040	0.010	0.040	0.001		73.80	47.12	25	45	168
WEDGE DISCO	759-07	ASTM A-276 GR 410	0.110	0.732	0.019	0.008	0.568	0.537	11.950	0.038	0.038	0.000		88.00	75.00	35	50	187

Sandra Ruiz

