

# QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)  
**ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO**

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PRABADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

API 598	- VALVE INSPECTION AND TESTING	API 6D	- PIPELINE VALVES - GATE, PLUG, BALL AND CHECK
API 599	- METAL PLUG VALVES - FLANGED, THREADED AND WELDING	API 600	- STEEL GATE VALVES, FLANGED AND WELDING ENDS
ANSI B16-10	- FACE TO FACE AND END TO END DIMENSIONS OF VALVES	ANSI B16-11	- FORGED FITTINGS, SOCKET - WELDING AND THREADED
ANSI B16-34	- VALVES - FLANGED, THREADED AND WELDING ENDS	API 602	- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS
MSS-SP61	- PRESSURE TESTING OF STEEL VALVES		

**Part No. FS011A1MABV80000Z**  
 (Código) **2" Fig. 1912 F WCB, V80000Z**

**Description** CAST STEEL SLAB GATE VALVE (API-6D) 150 PSI  
**Descripción** (VALVULA COMPUERTA PLANA DE ACERO FUNDIDO (API-6D) 150 PSI)

NACE-MR-01-75, FIRE TEST API 6FA (NORMA NACE-MR-01-75, PRUEBA DE FUEGO API 6FA)

PRESSURE TEST (PRUEBAS DE PRESION)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

**MECHANICAL TESTS (PROP. MECANICAS)**

CHEMICAL COMPOSITION (%)													COMPOSICIÓN QUIMICA (%)					
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	TENS KPSI CVN@	YIELD KPSI 1ST	ELG % 2ND	RED % 3RD	BHN AVG
<b>BODY</b> CUERPO	17528	ASTM A-216/WCB	0.190	0.730	0.017	0.016	0.470	0.080	0.070	0.060	0.080	0.010		76.70	40.74	27	38	164
<b>BONNET</b> BONETE	17528	ASTM A-216/WCB	Normalizated to (Normalizado a) 930 °C				Temper to (Temple a) 650 °C		Cooled in air.(Cooled in air. (Enfr)				76.70	40.74	27	38	164	
<b>WEDGE</b> DISCO	F9710	ASTM A-515 GR 70	0.190	0.730	0.017	0.016	0.470	0.080	0.070	0.060	0.080	0.010		77.43	42.92	24	40	185
			Normalizated to (Normalizado a) 930 °C				Temper to (Temple a) 650 °C		Cooled in air.(Cooled in air. (Enfr)									