

## QUALITY ASSURANCE CERTIFICATE OF COMPLIANCE

(ACCORDING TO EN10204 TYPE 3.1)

### ASEGURAMIENTO DE CALIDAD CERTIFICADO DE CUMPLIMIENTO

WE CERTIFY THAT THE PRODUCT LISTED BELOW WAS DESIGNED, MANUFACTURED AND TESTED ACCORDING TO OUR QUALITY SYSTEM AND REQUIREMENTS GIVEN IN ONE OR MORE OF THE FOLLOWING STANDARDS LAST EDITION:

(CERTIFICAMOS QUE EL PRODUCTO LISTADO ABAJO FUE DISEÑADO, FABRICADO Y PROBADO DE ACUERDO CON NUESTRO SISTEMA DE CALIDAD Y CON REQUISITOS ESTABLECIDOS EN UNO O MAS DE LOS SIGUIENTES ESTANDARES ULTIMA EDICIÓN.)

- |  |  |   |  |
|--|--|---|--|
| API 598<br>API 599<br>ANSI B16-10<br>ANSI B16-34<br>MSS-SP61 | - VALVE INSPECTION AND TESTING<br>- METAL PLUG VALVES - FLANGED, THREADED AND WELDING<br>- FACE TO FACE AND END TO END DIMENSIONS OF VALVES<br>- VALVES - FLANGED, THREADED AND WELDING ENDS<br>- PRESSURE TESTING OF STEEL VALVES | API 6D<br>API 600<br>ANSI B16-11<br>API 602 | - PIPELINE VALVES - GATE, PLUG, BALL AND CHECK<br>- STEEL GATE VALVES, FLANGED AND WELDING ENDS<br>- FORGED FITTINGS, SOCKET - WELDING AND THREADED<br>- COMPACT STEEL GATE VALVES - FLANGED, THREADED, WELDING AND EXTENDED - BODY ENDS |
|--|--|---|--|

**Part No. AC041A08MAA8300000**  
 (Código) **4" Fig. 5202 F UT WCB, API TRIM No.8 8300000**


**Description** CAST STEEL GATE VALVE 150 CLASS  
 Descripción (VALVULA COMPUERTA DE ACERO FUNDIDO CLASE 150)

VALVE WITH LOW EMISSION CONTROL (50 PPM'S MAX.) (VALVULA SUMINISTRADA CON CONTROL DE BAJAS EMISIONES FUGITIVAS (50 PPM'S MAX.))

PRESSURE TEST (PRUEBAS DE PRESTON)	SHELL (CASCO)	BACK (SEAT)	SIDE (LADO)	
			1	2
HYDROSTATIC (PSI) (HIDROSTATICA)	450	450	N A	N A
PNEUMATIC (PSI) (NEUMATICA)			80	80

#### MECHANICAL TESTS (PROP. MECANICAS)

CHEMICAL COMPOSITION (%)						COMPOSICIÓN QUIMICA (%)						TENS	YIELD	ELG	RED	BHN		
ITEM (PARTE)	HEAT No. (COLADA)	MATERIAL (ASTM)	C	Mn	P	S	Si	Ni	Cr	Mo	Cu	V	Cb	KPSI CVN@	KPSI 1ST	% 2ND	% 3RD	AVG
BODY CUERPO	WH6633	ASTM A-216/WCB	0.196	0.896	0.028	0.027	0.451	0.020	0.050	0.060	0.060	0.001		74.53	44.81	26	54	168
BONNET BONETE	WH3605	ASTM A-216/WCB	0.196	0.820	0.032	0.017	0.439	0.020	0.040	0.010	0.020	0.001		74.24	46.26	29	46	163
WEDGE DISCO	D3816	ASTM A-217/CA15	0.090	0.790	0.023	0.011	0.870	0.450	12.620	0.011	0.033	0.001		98.45	71.05	25	47	275
			Normalized to (Normalizado a) 930			Temper to (Temple a) 650			Cooled in air. (Enfriado en aire.)									
			Normalized to (Normalizado a) 930			Temper to (Temple a) 650			Cooled in air. (Enfriado en aire.)									
			Normalized a (Normalized to) 970			Temple a (Temper to) 630			Enfriado en aire. (Cooled in air.)									

  
 \_\_\_\_\_  
 Jessica García